

1 LOCATION OF WATER WELL: County: <u>Rice</u>	Fraction <u>1/4 NC 1/4 NE 1/4</u>	Section Number <u>24</u>	Township Number <u>T 20 S</u>	Range Number <u>R 9 E/W</u>
--	--------------------------------------	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

Approximately $3\frac{1}{4}$ miles south and $3\frac{1}{4}$ miles west of Lyons

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<u>Kenneth Knight</u> <u>1768 Avenue J</u> <u>Lyons, KS 67554</u>	Board of Agriculture, Division of Water Resources Application Number: <u>26,032</u>
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>58</u> ft. ELEVATION: <u>unknown</u>
--	--

N

	NW	NE
	SW	SE

S

W E

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 7-17-98

Pump test data: Well water was not ch'd ft. after hours pumping gpm

Est. Yield unknown gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter. 30 in. to 58 ft., and in. to ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded <u>X</u>
Blank casing diameter <u>16</u> in. to <u>29</u> ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height above land surface <u>12</u> in., weight <u>36.87</u> lbs./ft. Wall thickness or gauge No. <u>219</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) <u>Bridge slot</u>
SCREEN-PERFORATED INTERVALS: From <u>29</u> ft. to <u>57</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>58</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	<u>None known</u>
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	12	Sand and gravel, fine, medium			
12	15	Clay, brown			
15	34	Sand and gravel, fine, medium, some coarse			
34	37	Clay, brown			
37	56	Sand and gravel, fine, medium, some coarse, very loose			
56	58	Clay, brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-17-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>185</u> This Water Well Record was completed on (mo/day/yr) <u>7-21-98</u> under the business name of <u>Clarke Well & Equipment, Inc.</u> by (signature) <i>[Signature]</i>
--

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4