mw - 4 Form WWC-5 Division of Water Resources App. No. 1 WATER WELL RECORD Number | Township No. | Range Number | 3 | T | 20 | S | R | 9 | []E Section Number | Township No. 1 LOCATION OF WATER WELL: Fraction NW 5W 4 5W 4 NE 4 NE 4 County: Rice Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information: Latitude: 3.8..3.45.3.9.8...... (in decimal degrees) from nearest town or intersection: If at owner's address, check here ... Longitude: -9.8.312.1.7. (in decimal degrees) From intersection of US 56 Hwy & 10th Road, 1/4 mi. south to Elevation: facility Datum: WGS 84, NAD 83, NAD 27 2 WATER WELL OWNER: Collection Method: **NCRA** GPS unit (Make/Model:) RR#, Street Address, Box #: 2000 S. Main Street ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey City, State, ZIP Code McPherson, Ks. 67460 3 LOCATE WELL 4 DEPTH OF COMPLETED WELL 21 ft. WITH AN "X" IN (3)..... ft. SECTION BOX: Pump test data: Well water was......ft. after....... hours pumping....... gpm EST. YIELD......gpm. Well water was......ft. after......hours pumping...... gpm X NW -- -- NE --Bore Hole Diameter 8.25 in. toft., andin. toft. W WELL WATER TO BE USED AS: Public water supply Geothermal Injection well ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Domestic-lawn & garden ☑ Monitoring well ☐ Domestic ☐ Feedlot -- SE ---- SW --☐ Irrigation ☐ Industrial Was a chemical/bacteriological sample submitted to Department? Yes V No If yes, mo/day/yr sample was submitted..... S ----l mile------Water well disinfected? Yes No Other V PVC 5 TYPE OF CASING USED: Steel CASING JOINTS: Glued Clamped Welded Threaded TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Stainless Steel PVC None used (open hole) Other (Specify) Steel Brass Galvanized Steel SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify) ☐ None (open hole) SCREEN-PERFORATED INTERVALS: From 6 ft. to ...21 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 4 ft. to ...21 ft., From ft. to ft. to From. ft. to ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other

Grout Intervals: From 0 ft. to 6 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: Other (specify below) ☐ Lateral lines ☐ Pit privv ☐ Insecticide storage Livestock pens Septic tank Abandoned water well Cesspool Sewage lagoon Fuel storage Sewer lines Fertilizer storage Oil well/gas well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard Direction from well Distance from well FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS LITHOLOGIC LOG FROM TO 4 Clay, dark brown, silty, with top soil Silt, light gray, clayey, plastic 7 12 Silt, light brown, clayey, plastic 21 Clay, brown, silty, plastic 12

http://www.kdheks.gov/waterwell/index.html