<i>*</i>									
mw-5								ydysginnagyn is eeleksii seellisii ligdaan tayiin jä ein taatta talkaan oo	
WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.					
1 LOCATION County: Rice	OF WATER WELL:	Fraction SW NW 4NW 4 NE	NW 4 NE 4	,	n Number 4 3	Township No. 20		Number □E ☑W	
Street/Rural A	ddress of Well Location;	if unknown, distance &	direction	Globa	Positioning	System (GPS	(S) information	1:	
from nearest to	own or intersection: If at	owner's address, check	here .	Latitu	de:3.8	3449.86	(in de	cimal degrees)	
From intersection of US 56 Hwy & 10th Road, 1/4 mi. south to facility				Longitude:					
2 WATER WELL OWNER: NCRA					Datum: ☐ WGS 84, ☒ NAD 83, ☐ NAD 27 Collection Method:				
RR#, Street Address, Box #: 2000 S. Main Street				GPS unit (Make/Model:)					
City, State, Z	rm C 1	rson, Ks. 67460	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m						
3 LOCATE WEI	LL		. 00		0				
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 23 ft.							ft		
SECTION BOX: N Depth(s) Groundwater Encountered (1)									
		test data: Well water	r was	ft	after	hours p	oumping	gpm	
EST. YIELDgpm. Well water wasft. after hours pumping								gpm	
W NW 1 E Bore Hole Diameter 8.25									
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								well	
SW S	Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
SW - SE -									
s	If yes, mo	/day/yr sample was sub	mitted			Smarak			
1 mile		nfected? Yes 🗸							
5 TYPE OF CA	SING USED: Stee	el 🗹 PVC 🔲 (Other	,			<u></u>		
CASING IOINT	rs. □ Glued □ Cla	mned Welded	7 Threade	d				_	
Casing diamet	er .2 in. to .8	ft., Diameter	in.	to	ft., I	Diameter	in. to .	ft.	
Casing height	above land surface36	in., Weight		lbs./f	t., Wall thi	ckness or gaug	ge No990		
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)									
Brass Galvanized Steel None used (open hole)									
	ERFORATION OPENING	GS_ARE:	····	,			. 1. 1.3		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 8 ft. to 23 ft., From ft. to								ft.	
From							., ft. to	ft.	
GRAVEL PACK INTERVALS: From 6 ft. to .23 ft., From ft. to ft., From ft. to ft., From ft. to								ft.	
		From	ft. to	•	ft., From .		It. to	π.	
	TERIAL: Neat cem	nent [] Cement ground to .6 ft., Fron	Bento	nite L	Otner	From	ft to	ft	
Grout Intervals:	est source of possible con	tamination	1	. 11. 10		., * 10111		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Septic ta		ines Pit privy	Livestock	pens	☐ Insecticio	le storage	Other (speci	fy below)	
Sewer lines Cesspool Sewage lagoon Fuel storage						ed water well			
	th sewer lines Seepage	1 5	Fertilizer:		Oil well/g	-			
FROM TO	m well		FROM	TO	LITHO	OG (cont.) or	PLUGGING	INTERVALS	
0 4	Clay, dark brown, silty		1110171						
	soil	1 11111 100					in de parte, a prompta de parte parte de la constante de la constante de la constante de la constante de la co La constante de la constante d		
4 11	Clay, light gray, silty, i	olastic							
11 21	Silt, medium brown, c	layey, plastic					and the second s		
21 23	Clay & gravel, tan to r	nedium brown			<u> </u>				
	plastic			••••••••••••••••••••••••••••••••••••••					
			 		 				

INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at