

*This is well #6 8 well manifold system, wells are 75' apart, Est. Yield is all wells combined.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Rice	Fraction NW 1/4 SE 1/4 NW 1/4	Section Number 12	Township Number T 21 S	Range Number R 10 X 6W
---	----------------------------------	----------------------	---------------------------	---------------------------

Distance and direction from nearest town or city street address of well if located within city?
Approx. 3 miles west and 1/2 mi. south of Alden, KS

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Harold Ricker Route 1 - Box 9 Raymond, KS 67573	Board of Agriculture, Division of Water Resources Application Number: n/a
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION: unknown
--	--

N

---	---
NW	NE
---	---
SW	SE
---	---

S

Depth(s) Groundwater Encountered 1. 7 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 7 ft. below land surface measured on mo/day/yr 10/12/84

Pump test data: Well water was not ck'd ft. after hours pumping gpm

Est. Yield *1100 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 24 in. to 29 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded XX
Blank casing diameter . . . 16 in. to . . . 17 ft., Dia. 16 in. to . . . 29 ft., Dia in. to ft.			Threaded
Casing height above land surface . . . 12 in., weight 36, 87 lbs./ft. Wall thickness or gauge No. 219			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) Doerr Bridge Slot
SCREEN-PERFORATED INTERVALS: From . . . 17 ft. to . . . 25 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From . . . 10 ft. to . . . 29 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From . . . 0 ft. to . . . 10 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	FIELD
Direction from well? all			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	24	Sand & gravel, med. to coarse			
24	28	Tan clay			
28	29	Sand & gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/12/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 1/17/85 under the business name of Clarke Well & Eq., Inc. by (signature) <i>Clarke Well & Eq., Inc.</i>

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.