

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Stafford Fraction SE 1/4 SE 1/4 NE 1/4 Section Number 7 Township Number T 21 S Range Number R 11W EW

Distance and direction from nearest town or city street address of well if located within city? 4 E, 9 N of Hudson, Kansas

2 WATER WELL OWNER: Roy Schlochteemeier Stelring Drilling Co. Schlochteemeier A2-7 RR#, St. Address, Box #: Ellinwood, Ks. Box 129 Board of Agriculture, Division of Water Resources City, State, ZIP Code: 67526 Sterling, Kansas 67579 Application Number: 910-408

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 36-acre section box with an 'X' in the NE corner] 4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: Unknown. WELL'S STATIC WATER LEVEL: 35 ft. below land surface measured on 9/5/91. Pump test data: Well water was 60 gpm after 8 hours pumping. Bore Hole Diameter: 8 in. to 9.5 in. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 5 Wrought iron, 8 Concrete tile, CASING JOINTS: Glued, Clamped, Welded, Threaded. 2 PVC, 4 ABS, 7 Fiberglass, 9 Other (specify below). Blank casing diameter: 5 in. to 7.5 in., Dia. 12 in. to 2.8 in. Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 7 PVC, 8 RMP (SR), 10 Asbestos-cement, 2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole), 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 9 Drilled holes, 7 Torch cut, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft. GRAVEL PACK INTERVALS: From 20 ft. to 95 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 20 ft. What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well, 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below), 13 Insecticide storage. Direction from well? South How many feet? 60

LITHOLOGIC LOG and PLUGGING INTERVALS table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Row 1: 0 to 55, Sandy Clay. Row 2: 55 to 95, Sand and gravel.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/5/91 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 10/28/91 under the business name of Kelly's Water Well Service by (signature) [Signature]