WATE	CR WE	LL RECORD	Form V	WWC-5	Division of Water Resources App. No.	
1 LO	CATION	OF WATER WEL			Section Number Township No. Range Number	
	nty: Sta		<u> </u>	E 1/4 SE 1/4	6 T 21 S R 12 DE 7W	
Stre	et/Rural.	Address of Well Loc	ation; if unknown, distance	& direction	Global Positioning System (GPS) information:	
1	from nearest town or intersection: If at owne 7 3/4 South, 3 East of Great Bend			eck here	Latitude: (in decimal degrees)	
/ 3	/4 South	i, 3 East of Great B	lend		Longitude: (in decimal degrees)	
					Elevation:	
1			cott Salem		Collection Method:	
		Address, Box #: 20	025 NE 40 Avenue		GPS unit (Make/Model:	
City	y, State, 2	ZIP Code : EI	llinwood, KS 67526		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
3 LOC	CATE WE	ELL			Est. Accuracy:	
1	'H AN "X	"IN 4 DEPTI	H OF COMPLETED WE	LL 100	ft.	
SEC	TION BO	OX: Depth(s) (Groundwater Encountered	(1)	ft. (2) ft. (3) ft.	
<u> </u>	N	WELL'S	STATIC WATER LEVEL	ft.	ft. (2) ft. (3) ft. below land surface measured on mo/day/yr. 8-19-13	
		1 1	rump test data: well wa	ter was	If after hours numbing and	
w N	W N	EST. YIELD. N/Agpm. Well water was				
		T I WELL W	ATER TO BE USED AS	Public water	t, andt.	
67	ws	E ☐ Dome	stic	Oil field water	er supply	
13			ion 🔲 Industrial 🗸	Domestic-law	vn & garden Monitoring well	
اا	<u> </u>	Was a che	mical/bacteriological samp	le submitted to	Department? Tyes V1 No	
!	S 1 mile	If ye	es, mo/day/yr sample was si	ubmitted	*****************	
		water wer	Il disinfected? 🔽 Yes 🗆] No		
5 TYPE OF CASING USED: Steel V PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter 5 in. to 100 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.						
TYPE OF SCREEN OR PERFORATION MATERIAL: Weight ODINACO						
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)						
SCREE	Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 100 ft. to80 ft., From ft. to					
From the following the first the fir						
GRAVEL PACK INTERVALS: From100 ft. to 20 ff From ft to						
From						
Grout Intervals: From						
		est source of possible	contemination	m .49 H	t. to .9ft., Fromft. toft.	
What is the nearest source of possible contamination: Septic tank Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well House						
FROM	TO		DLOGIC LOG	The second secon	rom well75ft.	
0	4	Top soil	ALOGIC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
4	38	Sandy tan clay				
38	100	Sand & gravel- sm	nall to med			
		and the second s				
7 CONT	RACTO	R'S OR LANDON	VNER'S CEDITIFICATION	N. This		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) .8-19-13 and this record is true to the best of my knowledge and belief.						
Named Water Wolf Confidence Statement of the World December was assembled to 11. 7. 10. 90. 40						
under the business name of the positional data. Dettils and the bar (gianature)						
Telephone	Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. I related for a first one copy to WATER WELL OWNER and retain one for your records. I related for a first one copy to WATER WELL OWNER and retain one for your records.					
ZGA 00 1010						
NOA 82a-	-1212				Check: White Copy, Blue Copy, Pink Copy	