WATE	R WEI	LL RECORD	Form WWC-5	Division of Water Resources App. No.
		OF WATER WELL:	Fraction	Section Number Township No. Range Number
	ity: Stat		1/4 SE 1/4 NE 1/4 NE 1/4 if unknown, distance & direction	20 T 21 S R 12 E ☑W Global Positioning System (GPS) information:
			owner's address, check here .	Latitude: (in decimal degrees)
	orth of F			Longitude: (in decimal degrees)
	51111 01 1	1445011		Elevation:
2 WA	TER W	ELL OWNER: David B	unker	☐ Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 ☐ Collection Method:
RR#	, Street	,,	20th Avenue	GPS unit (Make/Model:)
City	, State, Z	IP Code : St. Johr	n, KS 67576	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL				
	H AN "X	" IN 4 DEPTH OF (COMPLETED WELL .120	
SECT	FION BO N	X: Depth(s) Ground	lwater Encountered (1)	ft. (2) ft. (3) ft below land surface measured on mo/day/yr. 3-28-14
ļ <u>, , , , , , , , , , , , , , , , , , ,</u>		WELL'S STATI	IC WATER LEVEL	ft. after hours pumping gpm
	v N		Agpm. Well water was	ft. after hours pumpinggpm
w N	V N	E Bore Hole Diam	eter 10in. to .120	ft., andin. toft.
				ter supply
sv	v s	E Domestic	☐ Feedlot ☐ Oil field wat	er supply
<u> </u>		Was a chemical	bacteriological sample submitted t	o Department? Yes No
S If yes, mo/day/yr sample was submitted				
1 mile Water well disinfected? ✓ Yes □ No				
5 TYPE OF CASING USED: Steel PVC Other				
CASING JOINTS: Glued ☐ Clamped ☐ Welded ☐ Threaded				
Casing diameter .5 in. to .120 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface .18 in., Weight .SDR-26 lbs./ft., Wall thickness or gauge No.				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
☐ Steel ☐ Stainless Steel ✓ PVC ☐ Other (Specify)				
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:				
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)				
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)				
SCREEN-PERFORATED INTERVALS: From				
GRAVEL PACK INTERVALS: From 120 ft. to 20 ft., From ft. to ft.				
From ft to ft From ft to ft				
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 20 ft., From ft., From ft. to ft.				
What is the nearest source of possible contamination:				
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)				
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☑ Oil well/gas well				
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☑ Oil well/gas well Direction from well				
FROM	ТО	LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0	4	Top soil		
4	28 46	Tan clay	and	
28 46	81	Sandy tan clay & fine s Tan clay	anu	
81	93	Blue clay		
93	100	Sand & gravel- small to	med	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged				
under my jurisdiction and was completed on (mo/day/year) .3-28-14 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 4-10-14				
under the business name of Rosencrantz-Bemis Ent Inc. by (signature) Communication (signature) C				
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.				
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html .				
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy				