WATER WELL R		WWC-5		sion of Water				
Original Record		e in Well Use		urces App. No.		Well ID		
,		Fraction  4 NW 4 SW 5		ion Number 12	Township Numbe		e Number	
2 WELL OWNER: La Business:		ural Address where well is located (if unknown, distance and n nearest town or intersection): If at owner's address, check here:						
Address: 1280 NE 4	7 3/4 South	·						
City: Hudson	1							
3 LOCATE WELL WITH "X" IN					5 Latitude: 38.2338 (decimal degrees) Longitude: 98.5987 (decimal degrees)			
SECTION BOX:	2) ft. 3) ft., or 4) ☐ Dry Well				Horizontal Datum: WGS 84 NAD 83 NAD 27			
	WELL'S STATIC WATER LEVEL:				Source for Latitude/Longitude:  GPS (unit make/model:)			
NWNE	above land surface, measured on (mo-day-yr)			(WAAS enabled? ☐ Yes ☐ No)				
W + E	Pump test data: Well v	☐ Land Survey ☐ Topographic Map ☐ Online Mapper:						
<b>y</b> -swse	Well v							
X	after hours pumping gpm  Estimated Yield:gpm			6 Elevation:ft. ☐ Ground Level ☐ TOC Source: ☐ Land Survey ■ GPS ☐ Topographic Map				
S	Bore Hole Diameter: 10 in. to 100 ft. and in. to 0ther							
7 WELL WATER TO BE USED AS:								
1. Domestic:	5. 🗌 Public Wa	ater Supply: well ID			eld Water Supply: lea			
☐ Household ☐ Lawn & Garden		ng: how many wells? . echarge: well ID		11. Test Hole: well ID				
Livestock	8. Monitoring: well ID							
2. ☐ Irrigation 3. ☐ Feedlot					d Loop			
3.								
Was a chemical/bacteriological sample submitted to KDHE?   Yes No If yes, date sample was submitted:								
Water well disinfected? ■ Yes □ No  8 TYPE OF CASING USED: □ Steel ■ PVC □ Other								
Casing diameter 5 in. to 100 ft., Diameter in. to ft., Diameter in. to ft., Diameter ft., Diameter in. to ft.								
Casing diameter								
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)								
SCREEN-PERFORATED INTERVALS: From100 ft. to80 ft., From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 100 ft. to 20 ft., From ft. to ft., From ft. to ft., From ft. to ft.								
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ■ Bentonite ☐ Other								
Nearest source of possible contamination:								
□ Septic Tank       □ Lateral Lines       □ Pit Privy       □ Livestock Pens       □ Insecticide Storage         □ Sewer Lines       □ Cess Pool       □ Sewage Lagoon       □ Fuel Storage       □ Abandoned Water Well								
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well								
Other (Specify)  Direction from well?								
10 FROM TO	LITHOLO		FROM		THO. LOG (cont.) or	PLUGGING	INTERVALS	
0 3 5	Sandy top soil							
	Soft sandy clay						to Catalogue to the table to table to the table to table to table to the table to tabl	
	<u>Gray clay</u> Sand & gravel- small	med clean coarse				<del> </del>	<del></del>	
<del></del>	Fan clay	mod Glodii Godii So						
	Sand & gravel- small	med clean coarse						
			Notes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year)								
under the business name of Rosencrantz- Bemis Ent Inc. Signature Dona Olyke								
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
Visit us at http://www.kdheks.gov/vaterwell/index.html  KSA 82a-1212  Revised 7/10/2015								