		ATER WELL:	Fraction			Section Numb			Range N	umber
	Stafford		SE ¼	SE 14	SW 1/4	31	T 21	S	R 13	E(V)
		on from nearest tow			located within	n city?				
		Seward Avenue		S						
_		WNER: J & R Se								
RR#, St. /	Address, Bo	x# : P.O. Box					_		ion of Water F	Resources
	e, ZIP Code		Kansas 6757'				Application No			
3 LOCAT	TE WELL'S	LOCATION 4	DEPTH OF COI	MPLETED WELL	L15	ft. ELE	EVATION:			
WITH /		ECTION BOX:	epth(s) Groundv	vater Encountere	ed 1		ft. 2	ft. :	3	ft.
Ā ſ	1	ï : v	VELL'S STATIC	WATER LEVEL		. ft. below land	surface measured	on mo/day/y	r	
	, ,		Pump t	test data: Well	water was	N.A ft.	after	. hours pun	nping	gpm
-	1	NE E					. after			
Wije W	•	1 B					., and			
E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 II							njection well	Ş		
, 1	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (S						Other (Specify	below)		
	SW	SE	2 Irrigation	4 Industrial	7 Lawn ar	nd garden only	10 Monitoring we		Vapor Obse	rvation.
	i x	i v	Vas a chemical/b	oacteriological s	ample submitt	ted to Departme	ent? YesNo.w	; If yes,	mo/day/yr sar	mple was
<u> </u>	, ,	s	ubmitted			V	Vater Well Disinfec	ted? Yes	No ·	vod S
5 TYPE	OF BLANK	CASING USED:	5	Wrought iron	8 C	oncrete tile	CASING JO	NTS: Glued	Clam	ped
1_S	teel	3 RMP (SR)	6	Asbestos-Cen	nent 9 0	ther (specify be	elow)		ed ,	
(2)P		4 ABS		7 Fiberglass				Threa	ded✔	
Blank casi	ing diamete	r	in. to 10.	ft., Dia.		in. to	ft., Dia		in. to	ft.
Casing he	ight above l	and surface	0 ir	n., weight	بير	lbs	s./ft. Wall thickness	or gauge N	o Sch.	.40
TYPE OF	SCREEN C	R PERFORATION!	MATERIAL			PVC	10 As	bestos-ceme	ent	
1 S	teel	3 Stainless s	teel 5	Fiberglass	8	RMP (SR)	11 Ott	ner (specify)		-
2 B	rass	4 Galvanized	steel 6	Concrete tile	9	ABS	12 No	ne used (ope	en hole)	
SCREEN	OR PERFO	RATION OPENINGS	S ARE:	5 0	auzed wrapp	ed	8 Sawcut		11 None (ope	en hole)
1 C	ontinuous s	lot (3)Mill	slot	6 V	Vire wrapped		9 Drilled holes			
2 L	ouvered shu	utter 4 Key	punched		orch cut		10 Other (specif			
SCREEN-	PERFORAT	ED INTERVALS:	From	10 ft. f	to 15	5ft., 1	From	ft.	to	ft.
			From	ft. t	to	ft., l	From	f t.	to	ft. ₇
C	GRAVEL PA	CK INTERVALS:					From			
			$\overline{}$				From			
	T MATERIA			Cement grout	_ (3) B		4 Other			
Grout Inte	rvals: Fro	m <u>0</u> ft	t. to 6	ft., From .	6	.ft.to	ft., From		. ft. to	ft.
What is th	ne nearest s	ource of possible c	ontamination:			10 Liv	estock pens	14 At	oandoned wate	r well
1 Sept	tic tank	4 Lateral	lines	7 Pit privy	/		el storage	15 Oi	i well/Gas well	
	er lines	5 Cess p		8 Sewage	_		rtilizer storage	16 Ot	her (specify b	elow)
		er lines 6 Seepag	ge pit	9 Feedya	rd		secticide storage			
Direction					. 500		nany feet?			
FROM	TO		LITHOLOGIC LO	JG	FRO	M TO	PI	LUGGING IN	IERVALS	
0	0.5	Gravel,		-11/4/			ļ			
0.5	3	Silt, Brown								
3	5	Silt, Brown								
5	9	Silt, Brown								
9	10	Clay, Brown G	гау							
10	15	Silt,								
.,,										
	-									
						-				
	-									
			- 4				VODW 2 T			
			***				VOBW-2, Flushm			
							Project Name: J ar	o K Service		
_	L						GeoCore # 355, #			
				= I= IO /	ell was (1) co		econstructed, or (3)			
		n (mo/day/year)					record is true to th		_ 7	
							as completed on (mo	/day/yr)	·// 5/29/9	6
under the	business na	ame of	GeoCore	Services, Inc	2	by (sigr	nature)	al la	lf_	
INSTRI Depart	UCTIONS: Use	e typewriter or ball point and Environment, Burea	pen. <i>PLEASE PRE</i> : u of Water, Topeka,	SS FIRMLY and <u>PR</u> Kansas 66620-0001	<u>INT</u> clearly. Plea . Telephone: 913	ase fill in blanks, un 3-296-5545. Send d	derline or circle the corre	oct answers. So WNER and retai	end top three copie n one for your rec	es to Kansas ords.

WATER WELL RECORD Form WWC-5 KSA 82a-1212