

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>	<u>SW 1/4 SW 1/4 SW 1/4</u>	<u>16</u>	<u>T 21 S</u>	<u>R 13 E/W</u>

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 east 3 north of Seward, Ks

2 WATER WELL OWNER: <u>Robert Tomlinson</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>1420 Hoover</u>	Application Number: <u>SFWW1425</u>
City, State, ZIP Code : <u>Great Bend, Ks. 67530</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL... <u>75'</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ... 28' ft. below land surface measured on mo/day/yr 11-22-99

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield NA gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter. 9 7/8 in. to 75' ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes HTH No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
<u>2 PVC</u>	4 ABS	7 Fiberglass	Threaded

Blank casing diameter ... 5 1/2 in. to 60 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface ... 2' in., weight ... SDR 26 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>7 PVC</u>	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:		From <u>60</u> ft. to <u>75</u> ft., From ft. to ft.	11 None (open hole)
GRAVEL PACK INTERVALS:		From <u>75</u> ft. to <u>20</u> ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>Hole plug</u>
-------------------	---------------	----------------	-------------	--------------------------

Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>House</u>

Direction from well? North West How many feet? 55'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Sandy top soil			
3	17	Fine sand			
17	24	Gray clay			
24	28	Brown clay			
28	30	Rusty brown clay			
30	50	Redish brown clay			
50	54	Brown and white clay and rock			
54	57	Sand and gravel			
57	62	Brown clay and sand mixed			
62	74	Sand and gravel medium loose			
74	75	Hard rock			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-22-99</u> and this record is true to the best of my knowledge and belief. Kansas	Water Well Contractor's License No. <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>12-4-99</u>
under the business name of <u>Rosencrantz-Bemis</u>	by (signature) <u>Media Pederson</u>

OFFICE USE ONLY

T

R

E/W

SEC

1/4

1/4

1/4