


1 LOCATION OF WATER WELL: County: Stafford	Fraction NE ¼ SW ¼ NW ¼	Section Number 34	Township Number T 21 S	Range Number R 13W E/W
--	---	-----------------------------	----------------------------------	----------------------------------

Distance and direction from nearest town or city street address of well if located within city?
2 1/2E of Seward, KS

2 WATER WELL OWNER: Ralph Stalcup	Sterling Drilling Company	R.S.L.#1
RR#, St. Address, Box # : 3218 Main St.	P. O. Box 1006	Board of Agriculture, Division of Water Resources Application Number:
City, State, ZIP Code : Great Bend, KS 67530	Pratt, KS 67124	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION: unknown
--	---



Depth(s) Groundwater Encountered 1 **18** ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL **18** ft. below land surface measured on mo/day/yr **10/24/05**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield **80** gpm: Well water was ft. after hours pumping gpm

WELL WATER ~~WAS~~ USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic ~~was~~ Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	Welded
<u>2 PVC</u>	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 5 in. to ft., Dia	60 in. to ft., Dia in. to ft., Dia in. to ft., Dia
Casing height above land surface 3 ft. below in., weight 2.8 lbs./ft.	Wall thickness or gauge No. Sch. 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	7 <u>PVC</u>
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
		10 Asbestos-Cement	
		11 Other (Specify)	
		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot		3 Mill slot	5 Guazed wrapped
2 Louvered shutter		4 Key punched	6 Wire wrapped
		7 Torch cut	
		8 <u>Saw cut</u>	
		9 Drilled holes	
		11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 60 ft. to 20 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 80 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 <u>Bentonite</u>	4 Other
GROUT INTERVALS: From 3 ft. to 20 ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			80	20	sand and gravel
			20	3	bentonite
			3	0	top soil

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **10/24/05** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **186**. This Water Well Record was completed on (mo/day/yr) **10/25/05** under the business name of **Kelly's Water Well Service, Inc.** by (signature) *Kathryn L. Good*