			WATE	R WELL RECORD	Form V	VWC-5	KSA 82			
⊣		TER WELL:	Fraction	77.00	272-		tion Number			Range Number
County: 1			NE 1/4		NW 1/4		16	т 21	S	R 13W E/W
			•	ddress of well if loca	ated within	city?				
1 E	, <u>3</u>	of Seward,			<u> </u>					
2 WATER			Boloser				ling			Division of Water Resources
1	Address, Bo									
	, ZIP Code									- Unknown -
3 LOCATE	WELL'S L									
ANX	IN SECTIO	<u> </u>								3
I T	· X	ı v	VELL'S STATIC	WATER LEVEL	15.	. ft. be	elow land su	ırface measured on r	no/day/yr	10/26/82
	. – NW – –	NE	Pump	test data: Well w	ater was		ft. :	after	hours pu	mping gpm
!! [1411	E	st. Yield60.	gpm: Well w	ater was		ft.	after	hours pu	mping gpm
• w	<u>i</u> .	E B	ore Hole Diame	eter8in.	to .7.5		ft.,	and	in	. to
A A F	Ţ.	i , v	VELL WATER T	O BE USED AS:	5 Publi	c water	r supply	8 Air conditioning	11	Injection well
[. – SW – –		1 Domestic	3 Feedlot	6 Oil fie	eld wat	er supply	9 Dewatering	12	Other (Specify below)
[] [35	2 Irrigation	4 Industrial	7 Lawn	and g	arden only	10 Observation well		
L	i	i v	Vas a chemical/l	oacteriological sampl	e submitte	d to De	partment?	/es <u>No.</u>	; If yes	, mo/day/yr sample was sub
		5 m	nitted				W	ater Well Disinfected	? Yes	_No
5 TYPE C	OF BLANK	CASING USED:		5 Wrought iron	8	Concre	te tile	CASING JOIN	TS: Glue	<u>d</u> Clamped
1 Ste	eel	3 RMP (SR)		6 Asbestos-Cemer	nt 9	Other (specify belo	ow)	Weld	ed
2 <u>PV</u>	C.	4 ABS		7 Fiberglass					Threa	aded
Blank casi	ng diameter	5in	n. to 55	ft., Dia		.in. to				in. to ft.
Casing hei	ight above I	and surface	12 .	.in., weight	.2.8		lbs	./ft. Wall thickness or	gauge N	oSch. 40
TYPE OF	SCREEN C	R PERFORATION	MATERIAL:			7_PV	2	10 Asbe	stos-ceme	ent
1 Ste	eel	3 Stainless s	steel	5 Fiberglass		8 RM	P (SR)	11 Other	(specify)	
2 Bra	ass	4 Galvanized	d steel	6 Concrete tile		9 ABS	3	12 None	used (op	en hole)
SCREEN (OR PERFO	RATION OPENING	S ARE:	5 Ga	uzed wrap	ped		8 Saw cut		11 None (open hole)
1 Co	ntinuous slo	ot 3 Mill	slot	6 Win	re wrapped	d		9 Drilled holes		
2 Lo	uvered shut	ter 4 Key	punched		rch cut					
SCREEN-	PERFORAT	ED INTERVALS:	From	55 ft. to	75		ft., Fro	om	ft. 1	toft,
			From	ft. to			ft., Fro	om	ft. 1	toft.
	GRAVEL PA	CK INTERVALS:	From	10 ft. to	75		ft., Fro	om	ft. 1	toft.
			From)					to ft.
6 GROUT	MATERIA	: 1 Neat ce	ment	2 Cement grout				Other		
Grout Inter	rvals: Fro	m 0 ft	. to .10	ft., From		. ft. 1	to	ft., From	.	ft. to ft.
1		ource of possible co						stock pens		bandoned water well
1 Se	ptic tank	4 Lateral	lines	7 Pit privy			11 Fue	storage	15 C	oil well/Gas well
2 Sewer lines 5 Cess pool			8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)				
3 Wa	atertight sev	ver lines 6 Seepag	ge pit	9 Feedyard	_		13 Inse	cticide storage .		
Direction f	rom well?	South	1	•			How m	any feet? 60		
FROM	TO		LITHOLOGIC	LOG	FR	ОМ	TO		ITHOLOG	SIC LOG
0	45	Clay		W 1001				. ,,		
45	75	Sand and Gr	avel							
							-			S CAMBELLY 18 MAIL 19 MINISTER CO. C.
										140.1.1.
					-					

Z CONTE	L		0.0557510.45	ON TI:						d
7 CONTE	RACTOR'S	OR LANDOWNER'S	S CERTIFICATI	ON: This water well	was (1) c	construc	cted (2) red	constructed, or (3) plu	igged un	der my jurisdiction and was
										nowledge and belief. Kansas
							-	on (mo/day/yr)	-	11/29/82
	business na		Kellys	Water Well	Service	e Tolocci	by (sign	ature)		e correct answers. Send top
										e correct answers. Send top . Send one to WATER WELL
55 50pic	and retain o	ne for your records.		DIVIOION DI LIVI	. J IOTIL, E			e, coolon, ropera, i	.5 55520	