

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Pawnee		NE 1/4 SE 1/4 SE 1/4	17	T 21 S	R 16 NE/W
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: Kevin Liston					
RR#, St. Address, Box #: Rt. 1 Box 119			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Larned, Ks. 67550			Application Number: PNW11434		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 11-23-99			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield NA gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 7/8 in. to 125 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No...X..... If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes HTH No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 5 in. to ft. Dia 95 in. to ft. Dia				8 Concrete tile	
Casing height above land surface 24 in. weight SDR 26 lbs./ft. Wall thickness or gauge No.				9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL:				CASING JOINTS: Glued X Clamped	
1 Steel		3 Stainless steel		5 PVC	
2 Brass		4 Galvanized steel		6 RMP (SR)	
				7 Asbestos-cement	
SCREEN OR PERFORATION OPENINGS ARE:				8 Other (specify)	
1 Continuous slot		3 Mill slot		9 ABS	
2 Louvered shutter		4 Key punched		10 None used (open hole)	
				11 None (open hole)	
SCREEN-PERFORATED INTERVALS:				12 Saw cut	
From 95 ft. to 125 ft.				13 Drilled holes	
				14 Other (specify)	
GRAVEL PACK INTERVALS:					
From 125 ft. to 20 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug					
Grout Intervals: From 20 ft. to 0 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
				House	
Direction from well? North East				How many feet? 53	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil	120	125	Broken sand rock and clay
3	11	Dark brown clay			
11	23	Gray sticky clay			
23	32	Dark brown and black clay			
32	37	Soft blue gray clay			
37	43	Sticky blue gray clay			
43	50	Soft brown gritty light gray clay			
50	54	Blue gray tough sticky clay			
54	60	Brown clay			
60	81	Soft brown sandy clay and rock mixed			
81	85	Tough brown clay			
85	95	Gritty brown soft clay			
95	100	Broken sand rock clay and sand mixed			
100	120	Gritty soft brown clay with fine sand rock			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-23-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 11-24-98 under the business name of Rosencrantz-Bemis by (signature) Fredia Dodson					