WATE	R WELL	RECORD	Form WWC	-5 D	ivision of W	Vater Reso	ources; App. No.		
1 LOC	ATION OF	WATER WELL:	Fraction SE ¼ SE ¼ or city street address	SW ¼	Section N	Number	Township Number T 21 S	Range Number	
Distance located w	and direction ithin city?	on from nearest town Larned / Pawnee Co.	or city street address Municipal Airport	of well if				rees, min. of 4 digits)	
2 WATER WELL OWNER: City of Larned						Latitude: Longitude: Elevation:			
RR#.	St. Address	. Box # : 417 Br	oadway		Datum:				
City,	State, ZIP C	ode : Larned	, KS 67550		Data Col				
1		L'S 4 DEPTH OI	COMPLETED WE	LL <u>45'</u>			ft.		
	ATON	Danah (a) Consu	-december Employment de d	261 0		A 2	Α 2		
1	I AN "X" I ION BOX	N Depth(s) Groun	ndwater Encountered l	30′ & F	ising	Ind our	II. 3	II.	
SECI	N N	WELL SSIA	FIC WATER LEVEL	1900.//	. IL DEIOW	lanu sum	hours numn	day/yr 8/9/0/	
l —	- 1 - 1	T Fet Vield	test data: Well wate gpm: Well wate	or was		after	hours pump	ing gpm	
	v NE	WELL WATE	R TO BE USED AS:	5 Public v	vater suppl	v 8 A	ir conditioning 11	Injection well	
1 1 1	' ''	1 Domestic 3	Feed lot 6 Oil field	l water su	pply	9 Dewa	atering 12 Oth	er (Specify below)	
w		E 2 Irrigation 4	Industrial 7 Domest	ic (lawn &	garden)	10 Mon	itoring well	(-1	
sy	v - + - · s¦E -								
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/								If yes, mo/day/yrs	
	S		bmitted						
5 TYPE	OF CASI	NG USED: 5	Wrought Iron	8 Conc	rete tile	CASI	NG JOINTS: Glued	Clamped	
1 St	eel	3 RMP (SR) 6	Asbestos-Cement	9 Other	(specify be	elow)	Welde	:d	
2 <u>P</u> V	<u>/C</u>	4 ABS 7	Fiberglass				Threa	ded X	
Blank cas	ing diamete	er 2 in. to	30 ft., Dia	.	in. to	ft.,	Dia in.	to ft.	
Casing he	ght above	land surface	Asbestos-Cement Fiberglass 30 ft., Dia in., Weight		lbs.	./ft. Wal	l thickness or gauge	No.	
1 1 Y P P () F	N KEEN	UK PERFUKATUN	INAIPKIAL						
2 Br	ass 4 Gal	vanized steel 6 Co	perglass 7 <u>PVC</u> ncrete tile 8 RM (S	R) 10	Asbestos-C	Cement	12 None used (one	n hole)	
SCREEN	OR PERF	RATION OPENIN	GS ARE:	,			-m 1 10111 11012 (opt		
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 45 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 28 ft. to 45 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
2 LO	DEDECT SAU	TED INTERVALS	d 6 wire wrapped	8 Sav	v Cut	10 Other	r (specify)		
SCREEN	-rekroka	TED INTERVALS.	From	ft to	45	A F	rom ft t	5 IL.	
GR	AVEL PA	CK INTERVALS:	From 28	ft to	45	ft. 17	rom ft t	o fi	
010	21122111	on nevi bievi bo.	From	ft. to		ft. F	rom ft. t	o ft.	
6 CDOI	TOT BALA OFF	DTAT. 1 Nagt com	ant 2 Cament arout	2 Pan	tonito	4 Other			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals From 1 ft. to 26 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:									
	tic tank	•	nes 7 Pit privy		tock pens	13 Ins	ecticide Storage	16 Other (specify	
	er lines	5 Cess pool		11 Fuels	torage	14 Ab	andoned water well	below)	
		er lines 6 Seepage p	it 9 Feedyard		_		l well/ gas well	Lust Site	
Direction	from well?	Southeast		How man	ny feet? 74	<u>'</u>			
FROM	TO	LITHOI	OGIC LOG	FROM	OT N		PLUGGING INTI	ERVALS	
0'	4'	Clay, black, moist.				ļ			
4'	14' 17'	Clay, very silty, br Clay, light brown,	own, low plasticity.			MW11			
17'	45'		own, low plasticity.	+		MINIT			
		014,1,011,011,1,01							
						ļ			
						+			
				- -		 			
			R'S CERTIFICATI	ON: This					
under my ji	arisdiction as	nd was completed on (r	no/day/year) 7/23/07		and this	record is	true to the best of my k	nowledge and belief.	
		tractor's License No.				completed	on (mo/day/year) 9	/13/07	
		of Coranco Great		_ by (sign		my	Che Make		
Geology Sec	tion, 1000 SW	Jackson St., Suite 420, T	correct answers. Send top opeka, Kansas 66612-1367	. Telephone	785-296-552	2. Send on	to WATER WELL OW	NER and retain one for	