WATER WELL RECORD	Form W	WC-5	· Di	vision of Wate	r Resources App. N	o. L	
1 LOCATION OF WATER W			1 '	on Number		Range Number	
County: Pawnee	SE 1/4 NE 1/4 NW			25		R 16 □E x □W	
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .			1	Latitude: (in decimal degrees)			
2 1/2E of Larned, KS				Longitude: (in decimal degrees)			
			Eleva	Elevation:			
2 WATER WELL OWNER: Ward Feed Yard				Datum: WGS 84, NAD 83, NAD 27			
RR#, Street Address, Box #: P. O. Box 1506			Collection Method: GPS unit (Make/Model:)				
City, State, ZIP Code :			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
and the second of the second o		Est. Accuracy:					
3 LOCATE WELL		2.5					
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL						_	
SECTION BOX: Depth(Depth(s) Groundwater Encountered (1)15						
N WELL	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
60							
I I I I I I I I I I I I I I I I I I I				ft. after hours pumping gpm			
W Bore Hole Diameter							
Demostic D Waster CV Oil field water sumply. D Devetoring D Other (Specify below)							
SWSE Domestic Feedlot Monitoring Dewatering Other (Specify below) Dewatering Other (Specify below) Dewatering Other (Specify below) Dewatering Domestic							
Was a chemical/bacteriological sample submitted to Department? Yes X No							
S If yes, mo/day/yr sample was submitted							
Water well disinfected? \(\) Yes \(\) No							
5 TYPE OF CASING USED: Steel X PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter							
Casing height above land surface. 3. ft. belown, Weight .2.8lbs./ft., Wall thickness or gauge NoSch40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
GRAVEL PACK INTERVALS: From 20 ft. to 35 ft., From ft. to ft.							
From							
6 GROUT MATERIAL: Neat cement Coment grout Bentonite Other.							
Grout Intervals: From							
What is the nearest source of possible contamination:							
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
Sewer lines							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well Distance from well							
	THOLOGIC LOG	, ,				ICCINIC INTERVALS	
FROM TO LIT	HOLOGIC LOG	FROM 35	TO 23		og (cont.) or PLC	JGGING INTERVALS	
WFY Unit #	1	23	3	gravel bentoni	to		
WIT OUT C #	1	3	0	top soi			
Sterling D	rilling Company	 	U	top soi	· · · · · · · · · · · · · · · · · · ·		
Sterling Drilling Company P. O. Box 1006		 					
Pratt, KS 67124							
11466, 83	57124						
		1					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was □ constructed, □ reconstructed, or ☒ plugged							
under my jurisdiction and was completed on (mo/day/year) . Q4/Q1/10 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No1.86 This Water Well Record was completed on (mo/day/year)04/.09/.10							
under the business name of .Kelly.'s. Water. Well. Service. Inc by (signature). Ha Mayor. J. Jon.							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							