			WATE	R WELL RECORD	Form W	WC-5 KS	A 82a-1	1212			
	ION OF WA	TER WELL:	Fraction	COE .	CC	Section Nu			ship Number	Range Number	
	Pawnee		NE 1/4	SE 1/4	SE 1/4	32		T	21 s	R 16 E(W)	
		from nearest town	•	ddress of well if loc	cated within o	city?					
		Street, Larned,									
2 WATE	R WELL OV	vner: Pawnee	Co. Coop	_							
RR#, St.	Address, Bo		st 3rd Stree	it.				Boa	rd of Agriculture	, Division of Water Resource	
City, State	e, ZIP Code	Larned,	Ks. 67550					App	lication Number:		
3 LOCAT	E WELL'S L	OCATION WITH 4	DEPTH OF C	OMPLETED WELL	26	ft. E	LEVAT				
AN "X"	IN SECTIO						ft. 2.		ft.	3	
ī [	1	l w	ELL'S STATIC	WATER LEVEL	16.25	ft. below	TCC	measu	red on mo/day/y	<sub>yr</sub> 03–16–93	
	NW		Pum	p test data: Well v	water was .		. ft. afti	er	hours p	oumping gpm	
	NW	NE   E								pumping gpm	
<u>.</u>	i		Bore Hole Diameter . 7, 7/8 in. to								
wile w	1	i w	WELL WATER TO BE USED AS: 5			5 Public water supply 8 Air condi					
7	1		1 Domestic	3 Feedlot	6 Oil fiel	d water supp	oly 9	Dewateri	ng 12	2 Other (Specify below)	
	SW	\$ <u></u>	2 Irrigation	4 Industrial	7 Lawn:	and garden (	only 🐠	Monitorin	ıg well		
1 1	i	l i lw	/as a chemical/	bacteriological samp	ple submitted	to Departme	nt? Yes	sN	lo. <b>v</b> ; If ye	es, mo/day/yr sample was sut	
1	(	s m	itted				Wate	er Well Dis	infected? Yes	No 🗸	
5 TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 C	oncrete tile		CASIN	IG JOINTS: Glu	ed Clamped	
1 St	teel	3 RMP (SR)		6 Asbestos-Ceme	ent 9 C	ther (specify	below)	ļ	Wei	lded	
(2)P\	VC	4 ABS	7 Fiberglass Threaded								
			. to	.11 ft., Dia						. in. to ft.	
		and surface									
TYPE OF	SCREEN O	R PERFORATION N	MATERIAL:		C	PVC		1	0 Asbestos-cem	nent	
1 St	eei	3 Stainless st	teel		8 RMP (SR)			11 Other (specify)			
2 Br	rass	4 Galvanized	<del>_</del>			ABS		12 None used (open hole)		• •	
SCREEN	OR PERFO	RATION OPENINGS	S ARE:	5 <b>G</b> /	auzed wrappe	ed		8 Saw cu	•	11 None (open hole)	
1 Cr	ontinuous slo	ot <b>3</b> Mill s			ire wrapped	• •		9 Drilled h		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
<b>2</b> Lc	ouvered shutt	_	punched		orch cut						
SCREEN-	PERFORATI	ED INTERVALS:				. 26 ft				toft.	
										toft.	
. (	GRAVEL PA	CK INTERVALS:								toft.	
			From	ft. to						to ft.	
	T MATERIAL		•	②Cement grout	<b>3</b> B	Bentonite	4 0	ther			
Grout Inte	rvals: From	m	to 6	ft., From	6	ft. to	. 9	ft., Fro	om	ft. to	
What is th	ie nearest <b>s</b> c	ource of possible cor	ntamination:			10 Livestoc			•		
1 Se	eptic tank	4 Lateral li	ines	ines 7 Pit privy		11 Fuel		storage		Oil well/Gas well	
2 Se	ewer lines	5 Cess po	ol	8 Sewage I	lagoon	oon 12 Fertilizer storage			16 (	16 Other (specify below)	
3 W	atertight sew	er lines 6 Seepage	e pit	9 Feedyard	1	13 Insecticide storage			е		
Direction f	from well?	northwest				Ho	w many	feet?	85		
FROM	то		LITHOLOGIC	LOG	FROI	м то			PLUGGING	INTERVALS	
<u> </u>	6"	sand and grave									
6"	י7	brown silty c	lay					-			
	25.5	fine to coarse	e sand/fine	to coarse grav	rel			OB2		And the contract of the contra	
25.5	26	brown silty c	lay								
										The second secon	
								or value. Addition of the	- 1996 - Tan I control transfer of desires ( material as	The mark field of the control of the	
										THE PERSONNEL PROPERTY OF THE LABOR STATES AND ADDRESS OF THE PERSONNEL PROPERTY OF THE PERSONNE	
CONTE	ACTOR'S C	OR LANDOWNER'S	CERTIFICATION	ON: This water well	was (1) cor	etructed (2)	racons	tructed or	(3) plugged up	der my jurisdiction and was	
	on (mo/day/									nowledge and belief. Kansas	
Mater Mal	I Controctor's	a License No. 57/		This Wester	Mall Dagge	1		(	-\ N217_	-03	
				This Water	· Well Record				1) 03-17-	<sup>593</sup>	
under the I	business nar	me of GeoCo	re Services	, Inc.		by (s	signatur	re) 💉	Jale A Ko	993. L e copies to Kansas Department	