


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Pawnee	NW 1/4 SW 1/4 SE 1/4	32	T 21 S	R 18 NE/W

Distance and direction from nearest town or city street address of well if located within city?

 $\frac{1}{4}$ south, $\frac{1}{8}$ west of Sanford, Ks.

2 WATER WELL OWNER:	Jim Froetschner	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	305 Morris	Application Number: PNo14
City, State, ZIP Code :	Larned, Ks. 67550	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 15.7 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 51. ft. below land surface measured on mo/day/yr 10-29-96
	Pump test data: Well water was 800 7.4 ft. after 1 1/2 hours pumping 800. gpm
	Est. Yield 1200. gpm: Well water was 90. ft. after 3 hours pumping 1200. gpm
	Bore Hole Diameter 28. in. to 15.7 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No <input checked="" type="checkbox"/>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 1.6 in. to 9.7 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 12" in., weight SDR 32.5 lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 9.7 ft. to 15.7 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 15.7 ft. to 20. ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	none
Direction from well?			How many feet?	none

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil			
3	33	Hard brown clay			
33	49	Sand and gravel			
49	51	Brown clay			
51	64	Fine sand with clay streaks			
64	80	Brown & green clay			
80	85	Soft brown clay			
85	99	Soft clay fine sand mixed			
99	102	Sand with clay streaks			
102	118	Sand and gravel with clay streaks			
118	121	Clay			
121	129	Fine sand with clay mixed			
129	157	Sand and gravel clean			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-31-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 11-5-96 under the business name of <u>Rosenerantz-Bemis</u> by (signature) <u>Fredia Rodson</u>
--