

1 LOCATION OF WATER WELL:		Fraction NW 1/4 SE 1/4 SW 1/4		Section Number 27		Township Number T 21 S		Range Number R 19 E 19	
County: Pawnee									
Distance and direction from nearest town or city street address of well if located within city? South Main Street, Rozell, KS (MW-3)									
2 WATER WELL OWNER:		Golden Plains Cooperative P.O. Box 68, South Main Street Rozell, KS 67574				Board of Agriculture, Division of Water Resources Application Number: 2071.79 ft. msl			
RR#, St. Address, Box #:									
City, State, ZIP Code:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 2071.79 ft. msl							
		Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 41.56 ft. below land surface measured on mo/day/yr 03/07/96							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm; Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 11.5 in. to ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter in. to ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface flush - 0 in., weight 0.7 lbs./ft. Wall thickness or gauge No. Sch 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 35 ft. to 50 ft.									
GRAVEL PACK INTERVALS: From 32.5 ft. to 50 ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 1 ft. to 32.5 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		Former UST Basin							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Fuel lines							
Direction from well?		How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 1 Gravel Fill									
1 9 Silty Clay: Brown, moist, with caliche.									
9 30 Silty Sand: Light Brown, fine grains, moist-wet									
30 34 Sand: Light Brown, medium grains									
34 36 Silt: Light Grey, saturated									
36 39 Silty Clay: Light Grey, very wet									
39 50 Sand: Light Brown, saturated at 42 ft.									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/05/96 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 524 This Water Well Record was completed on (mo/day/yr) 05/02/96									
under the business name of AEC, Inc. Allied Laboratories by (signature) [Signature]									