

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Pawnee		SE ¼ SE ¼ SE ¼	28	T 21 S	R 19 E/W
Distance and direction from nearest town or city street address of well if located within city? NW Corner of Hwy 156 & County Road - Rozel, Kansas					
2 WATER WELL OWNER: Don Shank					
RR#, St. Address, Box # : Rt. 1, Box 68			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Bazine, Kansas 67516			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: 999			
<p>1 Mile N NW NE SW SE X S</p>		Depth(s) Groundwater Encountered 1. 45 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL . . . 999 . . . ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was . . . NA . . . ft. after . . . hours pumping . . . gpm			
		Est. Yield . . NA . . gpm: Well water was . . . ft. after . . . hours pumping . . . gpm			
		Bore Hole Diameter . . . 8 . . in. to . . . 50 . . . ft., and . . . in. to . . . ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No✓..... If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No ✓			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 2 in. to 35 ft., Dia in. to ft., Dia in. to ft.				CASING JOINTS: Glued Clamped	
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. . . . Sch. 40				Welded	
TYPE OF SCREEN OR PERFORATION MATERIAL				Threaded. ✓	
1 Steel		3 Stainless steel		7 PVC	
2 Brass		4 Galvanized steel		10 Asbestos-cement	
				11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		3 Mill slot		11 None (open hole)	
2 Louvered shutter		6 Wire wrapped		9 Drilled holes	
4 Key punched		7 Torch cut		10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 35 ft. to 50 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 34 ft. to 50 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From 0 ft. to 32 ft., From 32 ft. to 34 ft., From ft. to ft.				4 Other	
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		10 Livestock pens	
2 Sewer lines		5 Cess pool		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		12 Fertilizer storage	
		7 Pit privy		13 Insecticide storage	
		8 Sewage lagoon		14 Abandoned water well	
		9 Feedyard		15 Oil well/Gas well	
Direction from well? Unknown				16 Other (specify below)	
				Former UST Basin	
				How many feet?	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil, Dark Brown			
2	7	Silt, Dark Brown			
7	12	Silt, Light Brown			
12	17	Silt, Light Brown			
17	22	Sand, Light Brown			
22	27	Sand, Light Brown			
27	32	Sand, Light Brown			
32	37	Sand, Light Brown			
37	42	Sand, Light Brown			
42	50	Sand, Light Brown			
					MW5, Flushmount
					Project Name: Larsen-Rozel
					GeoCore # 404
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/27/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 1/10/97 under the business name of GeoCore Services, Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					