LOCATION OF WATER WELL:	WATE! Fraction	R WELL RECORD For		KSA 82a-1 on Number		r Range Number	
ounty: Pawnee		SE 1/4 SF	1/4 Gecti			R 19 EAN	
stance and direction from nearest							
			 			Middlette, til den stadsellet i syklemensk som eksesserbyr og pyrer og gyges at geste stælsk skalen.	
WATER WELL OWNER: Don		VE	WI				
R#, St. Address, Box # : P.O.	Box 27					e, Division of Water Resources	
ity, State, ZIP Code : Burc	lett, KS 67523	The Store	-Rozel		Application Number	:	
ILOCATE WELL'S LOCATON WI	TH!.!						
AN "X" IN SECTION BOX:	DEPTH OF C	OMPLETED WELL	43	it. ELE	VAHON:	ft. 3ft.	
	Depth(s) Groundy	vater Encountered 1		f	. 2	ft. 3 ft.	
1						o/day/yr	
	Pump	test data: Well water	was		ft, afterho	ours pumping gpm ours pumping gpm in. to ft 11 Injection well	
	Est. Yield	gpm: Well water	was		ft, after ho	ours pumping gpm	
∯ W	E Bore Hole Diame	ter 8 in to	43		ft, and	in. to ft. 11 Injection well 12 Other (Specify below)	
	WELL WATER TO	O BE USED AS: 5 Pu	blic water su	ipply	8 Air conditioning	11 Injection well	
	1 Domestic	3 Feed lot 6 Oil	field water s	supply	9 Dewatering	12 Other (Specify below)	
1 1 1 1 1 7							
*	Was a chemical/b	pacteriological sample su	ubmitted to D	epartment?	Yes No X I	If yes, mo/day/yr sample was	
S	submitted			Wa	ter Well Disinfected? Y	es No X	
TYPE OF BLANK CASING USE):	5 Wrought Iron				Glued Clamped	
		6 Asbestos-Cement				Welded	
2 PVC 4 AB						Threaded X	
Blank casing diameter 4			in +		ft Dia	in to 4	
asing height above land surface		in., weight 2	.071	lbs./ft.	Wall thickness or gauge	e No237	
VDE OF SOBEEN OD BEDEODAT	ION MATERIAL.		7	DVC	10 Ashantas	aam ant	
1 Steel 3 Sta	inless steel	5 Fiberglass	8	RMP (SR)	11 Other (spe	ecify)	
2 Brass 4 Ga	vanized steel	6 Concrete tile	9	ABS	12 None use	a (open noie)	
CREEN OR PERFORATION OPE 1 Continuous slot	NINGS ARE: 3 Mill slot	5 Gauze	d wrapped rapped		8 Saw cut	11 None (open hole)	
2 Louvered shutter		7 Torch	rapped		9 Drilled notes		
SCREEN-PERFORATED INTERVA	* *				To Other (specify)	# 4- B	
SCREEN-FERFORATED INTERVA						ft. to ft.	
ODAVE BLOWNERS	⊢rom	nt, to		tt.	-rom -	ft. toft.	
GRAVEL PACK INTERVAL						ft. to ft.	
	From	ft. to		ft.	From	ft. to ft.	
GROUT MATERIAL: 1 Ne	at cement 2	Cement grout	3 Bent	tonite	4 Other		
Grout Intervals From 2	ft. to 19	ft. From 19	ft. t	o 21	ft. From	ft. to ft.	
What is the nearest source of possit	le contamination:					4 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel	storage 1	5 Oil well/ Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Ferti	izer storage 10	16 Other (specify below)	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard				interminated Att	
Direction from well?	.	-		How many		y	
FROM TO CODE	LITHOL	OGIC LOG	FROM	ТО		NG INTERVALS	
	Cement		I	L			
	Gray silty clay						
11 22	Brown silty clay	1					
22 42.5	Fine grain silty,	, clayey, sand					
42.5 45	<u>Fine to med sau</u>	nd, scattered					
	gravel						
1 1 1		**************************************	<u> </u>	<u> </u>			
							
			ļ				
			1				
				<u> </u>			
, CONTRACTOR'S OR LANDOW	NER'S CERTIFICATION	ON: This water well was	s (1) construc	cted, (2) rec	onstructed, or (3) plugge	ed under my jurisdiction and	
was							
/was completed on (mo/day/yr)	02/0	B/02	and thi	is record is t	rue to the best of my kn	owledge and belief. Kansas	
was	02/0	B/02	and thi	is record is t /ater Well R	rue to the best of my kno		