WATE	R WEI	LL RECORD	Form W	WC-5	Division of Water	Resources App. No	
1 LOC	ATION	OF WATER WELL:			Section Number	Township No.	Range Number
	ty: Paw		1/4 SE 1/4 NE		36	T 21 S	R 19 □E 🗹 W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here							
					Latitude:		
1 3/4 West of Sanford					Elevation:		
2 WATER WELL OWNER: Kerry Froetschner					Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: Kerry Froetschner RR#, Street Address, Box #: 1321 250th Avenue					Collection Method: GPS unit (Make/Model:)		
City, State, ZIP Code : Rozel, KS 67574					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
				Est. Accuracy: <	3 m, 3-5 m,	5-15 m,	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 120 ft.							
SECTION BOX: Depth(s) Groundwater Encountered (1)							3) ft.
N WELL'S STATIC WATER LEVEL51ft. below land surface measured on mo/day/yr8-27-13							
Pump test data: Well water wasft. after							
NW NE D							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
Swall SF X Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
Irrigation Industrial Domestic-lawn & garden Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
water well disinfected? \(\overline{\mathrm{A}} \) Yes \(\overline{\mathrm{N}} \) No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .5 in. to .120 ft., Diameter in. to ft., Diameter in. to ft.							
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)							
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)							
From							
GRAVEL PACK INTERVALS: From 120 ft. to 90 ft. From ft. to ft.							
From . 85							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 90 ft. to 85 ft., From 20 ft. to 0 ft.							
					u. 10 n.,	riom	. It. 10
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Shed Direction from well South ☐ Distance from well .15ft.							
FROM	TO	LITHOLOG		FROM			GGING INTERVALS
0 4 43	4	Top soil					
4	43	Tan clay		<u> </u>			
43	68	Sand & gravel- med	1 0				
68 94	94 120	Clay w/ streaks of sand Sand & gravel/ few clay		+			
34	120	Garia & graver lew cla	y streaks				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .9-13-13 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 10-7-13							
under the business name of Rosencrantz-Bemis Ent. Inc. by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone	785-296-	5524. Send one copy to WAT					
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Deline Copy							
MUN 048	-1212				CHECK.	ine copy, 🗀 Bit	с сору, 🗀 гиж сору