

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: McPherson		SE ¼ SW ¼ SE ¼	22	T 21 S	R 2 EW
Distance and direction from nearest town or city street address of well if located within city? Northwest Corner of Cole and Drucilla					
2 WATER WELL OWNER:		Mid-Kansas Co-op		01968024 MW-2 Deep	
RR#, St. Address, Box # :		307 West Cole		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Moundridge, Kansas		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: Approx Surface 1485			
Diagram: A square divided into four quadrants labeled NW, NE, SW, and SE. An 'X' is marked in the SE quadrant.		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 12/18/96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8.25 in. to 35 ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
(2) PVC 4 ABS		Threaded. X			
Blank casing diameter 2 in. to 30 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface. -2 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		(7) PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass		8 RMP (SR) 11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile		9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot (3) Mill slot 6 Wire wrapped		9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 30 ft. to 35 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 28 ft. to 35 ft., From ft. to ft.					
6 GROUT MATERIAL: (1) Neat cement 2 Cement grout (3) Bentonite 4 Other					
Grout Intervals: From 0 ft. to 26 ft., From 26 ft. to 28 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		13 Insecticide storage			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10.0	Silty, Lean to Fat Clay, Brown			
10.0	22.0	Silty Lean Clay, Gray			
22.0	35.0	Clayey, Fine to Medium Sand, Brown			
35.0		Shale, Olive to Red-Brown			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/9/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/year) 12/9/97 under the business name of Terracon Consultants, Inc. by (signature) <i>[Signature]</i>					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.