


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Mepherson	Fraction SE 1/4 SE 1/4 NW 1/4	Section number 26	Township number 21	Range number 2 W
2. Distance and direction from nearest town or city: SE corner of Moundridge Ks.		3. Owner of well: Floyd Bradberry		R.R. or street: 739 Parklane		
Street address of well location if in city:		City, state, zip code: Moundridge Ks. 67107				
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 10 in. Completion date 7/11/76		
				Well depth 42 ft.		
5. Type and color of material		From	To	7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug		
topsoil-black		0	2	<input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
clay- dark gray		2	9	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry		
clay light gray		9	18	<input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock		
sand coarse- gray		18	23	<input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
shale light green/layers of red		23	32	9. Casing: Material plst Height: Above or xxxx		
shale dark red		32	36	Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in.		
shale dark gray		36	42	RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 1.95 lbs./ft.		
				Dia. 6 in. to 42 ft. depth Wall Thickness: inches or		
				Dia. 6 in. to 42 ft. depth gage No. .200		
				10. Screen: Manufacturer's name J&L		
				Type RMP Dia. 6"		
				Slot/gauze 3/32" Length 20"		
				Set between 17 ft. and 37 ft.		
				Gravel pack? yes Size range of material F-1/2"		
				11. Static water level: 12 ft. below land surface Date 7/11/76		
				12. Pumping level below land surfaces:		
				21 ft. after 3 hrs. pumping 25 g.p.m.		
				30 ft. after 30 hrs. pumping 30 g.p.m.		
				Estimated maximum yield 30 g.p.m.		
				13. Water sample submitted: mo./day/yr.		
				<input type="checkbox"/> Yes <input type="checkbox"/> No Date 7/11/76		
				14. Well head completion:		
				<input checked="" type="checkbox"/> Pitless adapter 12 inches above grade		
				15. Well grouted? yes		
				With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete		
				Depth: From 3 ft. to 13 ft.		
				16. Nearest source of possible contamination:		
				ft. 50 Direction N Type sewer 1		
				Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump:		
				Manufacturer's name Aermotor Not installed		
				Model number SD19 HP 3/4 Volts 230		
				Length of drop pipe 30 ft. capacity 25 g.p.m.		
				Type:		
				<input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine		
				<input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating		
				<input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:				
Topography:						
<input type="checkbox"/> Hill						
<input checked="" type="checkbox"/> Slope						
<input type="checkbox"/> Upland						
<input type="checkbox"/> Valley						
		20. Water well contractor's certification:				
		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
		Miller Water Well Serv. 137				
		Business name Hutchinson, Kansas 67501				
		Address 739 Parklane				
		Signed Joe Miller Date 7/11/76				
		Authorized representative				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5