WATED WET	LL RECORD MW-22 Form WWC-5	rivision of Water Resources App. No.
		ion Number Township No. Range Number
	101 1111111111	22 T 21 S R 2 DE WW
County: McF		al Positioning System (GPS) information:
Street/Rural A	, , , , , , , , , , , , , , , , , , , ,	tude: 38.20405 (in decimal degrees)
from nearest 1	town or intersection: If at owner's address, check here . Latin	(in decimal degrees)
124 N. Druc	icilla Moundridge, KS	gitude: -97.52355 (in decimal degrees)
	Elev	ration:
A NATA OCURATO NAT	Datu Datu	<u>m</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27
		ection Method:
		GPS unit (Make/Model:
City, State, Z	ZIP Code : Moundridge, KS 67107 L	Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
		Accuracy: <5 m, 5-5 m, 5-15 m, >15 m
3 LOCATE WE	A TO THE PROPERTY OF THE PROPE	£
WITH AN "X	WIN 4 DEPTH OF COMPLETED WELL	
SECTION BO	Depth(s) Groundwater Encountered (1).18 ft WELL'S STATIC WATER LEVEL 18.77 ft. below	(2)t. (3)t.
N	WELL'S STATIC WATER LEVEL	land surface measured on mo/day/y1. 9/9/.17
	Pump test data: Well water was	ft. after hours pumping gpm
EST. YIELDgpm. Well water wasft. after hours pumpinggpm		
W		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)		
Industrial Domestic-lawn & garden Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No		
s If yes, mo/day/yr sample was submitted		
1 mile		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter 2 in. to .30		
Casing height above land surface		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel PVC ☐ Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERF	FORATED INTERVALS: From 15 ft. to 30	ft., From ft. to ft.
From		
GRAVEL PACK INTERVALS: From 13 ft. to 30 ft., From ft. to ft.		
From ft. to ft., From ft. to ft.		
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other		
Grout Intervals: From 1.5 ft. to		
	rest source of possible contamination:	
Septic ta		☐ Insecticide storage ☐ Other (specify below)
Sewer li	lines Cesspool Sewage lagoon Fuel storage	Abandoned water well
Watertig	ight sewer lines Seepage pit Feedyard Fertilizer storage	Oil well/gas well
Direction from	ight sewer lines Seepage pit Feedyard Fertilizer storage om well Southwest, south, southeast Distance from well	well <100 feet
FROM TO	LITHOLOGIC LOG FROM TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0 1.5	Gravel, asphalt, organics (Fill)	
1.5 7	Dark brown clay	
	Red clay with silt	
11 13	Gray clay with silt	
13 16	Red clay with silt	
16 18	Red clay, very stiff	- WHAT MAN AND AND AND AND AND AND AND AND AND A
18 20	Red silty clay, soft, wet	
20 30	Sandy clay and clayey sand	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year) 6/5/14 and this record is true to the best of my knowledge and belief.		
Kaneae Water W	Well Contractor's License No. 416 This Water Well Record	was completed on (mo/day/vear) 7/14/14
under the busine	ness name of Terracon Consultants, Inc. by	(signature)
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies		
(white blue nink)	to Kansas Department of Health and Environment, Bureau of Water, Geology Sec	tion, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.
Telephone 785-296	6-5522. Send one copy to WATER WELL OWNER and retain one for your rec	cords. Include fee of \$5.00 for each constructed well. Visit us at
http://www.kdheks.	s.gov/waterwell/index.html.	The same of the sa
KSA 82a-1212		Check: 🗌 White Copy, 🔲 Blue Copy, 🔲 Pink Copy