304 12085 Domestic WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Pawnee	Fraction 1/4 SE 1/4 SW 1/4 SW 1/4	Section Number Township No. Range Number T 21 S R 20 DE W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here Approximately 2 miles north and 2 miles west of Burdett. 2 WATER WELL OWNER: Junior Dean Cooper		Global Positioning System (GPS) information: Latitude: 38.218761 (in decimal degrees) Longitude: -99.56649 (in decimal degrees) Elevation: Unknown Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27
RR#, Street Address, Box #: 3678 Q Rd. City, State, ZIP Code : Burdett, KS 67523		Collection Method: ☐ GPS unit (Make/Model: WAAS ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL WITH AN "X" IN SECTION BOX: N Lepth(s) Groundwater Encountered (1) WELL'S STATIC WATER LEVEL WELL'S STATIC WATER LEVEL Fig. 102 Pump test data: Well water was not checked ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 105 ft., and in. to ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water well disinfected? Yes No		
STYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in. to 90 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in., Weight 2.36 lbs./ft., Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
SCREEN-PERFORATED INTERVALS GRAVEL PACK INTERVALS	3: From 24 ft. to 10	Other (specify) ft., From ft. to ft.
From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 4 ft. to 24 ft., From ft. to ft. From ft. to ft.		
What is the nearest source of possible contamination: Septic tank Sewer lines Sewer lines Watertight sewer lines Direction from well What is the nearest source of possible contamination: Livestock pens Fuel storage Abandoned water well Fertilizer storage Oil well/gas well Distance from well North Distance from well		
FROM TO LITHOLO 0 3 Topsoil	GIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
3 35 Clay, brown		
35 47 Sand, gravel, fine 47 60 Clay, gray, black		
60 75 Sand, gravel, fine to	medium	
75 78 Clay, brown 78 87 Clay, gray		
78 87 Clay, gray 87 100 Sand, gravel, fine to	coarse	
100 105 Clay, brown	odarse	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 12/03/12 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 12/07/12 under the business name of Clarke Well & Equipment, Inc. by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html. Check: White Copy Blue Copy		