USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

BURDETI

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

		DDB				Торе	eka, Kansas 66620		
	County			Section number		Township number Range number			
1. Location of well:	Hodgman	NW/SE/1/4SE	1/4	23		r 21 s	R 21	E. (V)	
2. Distance and dire	ction from nearest town or city: 2		3. Owner o	f well	· Ed	Eakin			
2. Distance and direction from nearest town or city: $2N-4w-3454$ 3. Owner of v. R.R. or street address of well location if in city: Byrae Tre City, state, z.									
DURACTTE City, st					6. Bore hole dia 108 in. Completion date				
4. Locate with "X" i		ketch map:				6. Bore hole dia 27 in. Well depth 108 ft.	10-15-76		
i !]	!					7 Cable tool X Rotary	Driven Dug		
NW NE					Hollow rod Jetted Bored Reverse rotary			rse rotary	
© W						8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other			
SW SE						9. Casing: MaterialSteel Height: Above or below Threaded Welded Surface in.			
<u> </u>						Threaded Welded iSurface in. RMP PVC Weight lbs./ft.			
S 1 M				<i>i</i> .	5 x 2 1	RMP PVC	weight th!Wall Thickness: in	_IDS./ff.	
5. Type and color of material				rom	То	Diain. to ft. depth gage No7			
		5.35°				10. Screen: Manufacturer's n Johnson and Do	ame	—	
Ø Top Soi	1		()	3	Type Steel	_ Dia. <u>16</u> _		
Clay				3	43	Slo ygauze 3/16 Length 14 & 18 Set between 18 @ 71½ft. and 89½ ft.			
						Set between 10 6 /12 14 @ 93 ft. o	iff. and <u>095</u> and <u>108</u>	ft.	
Blue Sand and Gravel				+3	71	14 @ 93 ft. and 108 ft. Gravel pack? X Size range of material			
Good Clean Sand and Gravel				71	87	11. Static water level: mo./day/yr. 45 ft. below land surface Date 8-17-76			
Clay				37	87 ½	12. Pumping level below land surfaces:			
Good Clean Sand and Gravel				37 <u>‡</u>	89				
Clay				39	90	13. Water sample submitted: mo./day/yr.			
Good Clean Gravel				90	95	X Yes No Date 8-17-76 14. Well head completion:			
Clay				95	100	Pitless adapter Inches above grade			
Good clean Sand and Gravel				100	(109)	15. Well grouted? Bentonite _X Concrete _			
Fire				109		Depth: From ft. to ft. 16. Nearest source of possible contamination:			
BROCK 109' 2R-						ft. 1/2 Direction NW Type corrall Well disinfected upon completion? Yes No			
	45					17. Pump: W.J. T	Not installed	_₹	
64' sat thick						Manufacturer's name W • L • R • Model number 3 BHC 12 HP 60 Volts			
in Allavian							ft. capacity 120		
						Type:	X_ Turbine		
						Submersible Jet	Recipro	1	
(Use a second sheet if needed)						Centrifugal	Other	Sec	
18. Elevation: 19. Remarks:						20. Water well contractor's of This well was drilled under my		report	
						is true to the best of my know		- 1	
Topography: 7122						Rosenerantz Ben	121	_	
Hill Slope							Bend, Ks.	67530 =	
x Upland	20	13 6	Tar	**		Signed Fredia.	Lackon Date	11/8/2	
Valley			(01)			Authorized rep	resentative	4	