

1 LOCATION OF WATER WELL: Fraction N/C 1/4 NW 1/4 NE 1/4 Section Number 36 Township Number T 21 S Range Number R 21 SW

Distance and direction from nearest town or city street address of well if located within city? 3 3/4 south, 2 3/4 east of Gray Ks.

2 WATER WELL OWNER: Gertrude Klein RR#, St. Address, Box #: Rozel, Ks. 67574 Board of Agriculture, Division of Water Resources City, State, ZIP Code: Application Number: HG0015

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants and an 'X' in the NE quadrant.] 4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: ... WELL'S STATIC WATER LEVEL 46 1/2 ft. below land surface measured on mo/day/yr 11-29-89

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 16 in. to 62 ft. Dia 16 in. to 67 to 75 ft. Dia Casing height above land surface 12 in., weight SDR: 32.5 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 62 ft. to 67 ft., From 75 ft. to 95 ft. GRAVEL PACK INTERVALS: From 20 ft. to 95 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage old Plugged well Direction from well? south How many feet? 54'

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-3 Top soil, 3-35 Brown clay, 35-55 Sand and gravel, 55-58 Blue clay, 58-65 Sand and gravel buff colored coarse and loose, 65-77 Soft brown sandy clay, 77-92 Sand and gravel loose clean coarse, 92-95 Fire clay.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-27-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 1-22-90 under the business name of Rosencrantz-Bemis by (signature) Fredia Nelson

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R EW SEC. 1/4 1/4 1/4