USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

HORSE THIEF CHINYON NE

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| A CC | | | | Topeka, Kansas 66620 | | | |
|--|---|---------|----------------|----------------------|--------------------------------|--|---|
| | County Fraction Hodgeman SW 1/4 SW 1/4 NE 1/4 | | Section number | | Township number | Range number | |
| 1. Location of well: | | | | | т 21 s | R 25 EW | |
| Distance and direction from nearest town or city: | | | | | : | J. D. Nuss | |
| 8W, 11N, 4E, 4N, 4E of Jetmore Street address of well location if in city: | | | | street: | | T . 170 | Coorle |
| City, ste | | | | tate, zip code: | | Jetmore, KS | |
| 4. Locate with "X" in section below: Sketch map: N | | | | | | 6. Bore hole dia. 28 in Well depthft. | . Completion date |
| i i | | | | | | 7 Cable tool Rotary | Driven Dug |
| | | | | | | | Bored XReverse rotary |
| | | | | | | 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other | |
| f_ | | | | | | | |
| | | | | | | 9. Casing: Material stee | Height: Above or below |
| | | | | | | Threaded Welded Surface in. RMP PVC Weight lbs./ft. Dia ft. depth Wall Thickness: inches or | |
| S. | | | | | | | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. dep | |
| 3. Type and color or | material | | | FFOIII | - 10 | 10. Screen: Manufacturer's | name |
| g | of a co | | | 0 | Q | W. A. Bros | 16 1 |
| Surface | | | | | | Type <u>Bridge</u> Slot/gouze <u>188</u> | Dia10 Length20 |
| Clay | | | | 3 | 15 | Set between 34 | _ft. andft. |
| Sand "dry" | | | | 15 | 22 | Gravel pack? X Size ro | andft. ange of material 1/4 to 5/8 |
| Clay & Streaks of Sand | | | | 22 | 28 | 11. Static water level: 31 ft. below land su | mo./day/yr. rface Dote <u>12-17-76</u> |
| $\mathtt{C}_{\mathtt{lay}}$ | | | 28 | 31 | 12. Pumping level below lan | d surfaces: | |
| | | | 31 | 38 | | hrs. pumping350g.p.m. | |
| Med. Sand & Gravel | | | |)1 | <u></u> | Estimated maximum yield — | hrs. pumping g.p.m. |
| Clay | | | | 38 | 41 | 13. Water sample submitted: | • |
| Sand & Gravel | | | | 41 | 5/4 | Yes X No 14. Well head completion: | Date |
| Hard Rock | | | | (54) | 57 | Pitless adapter | 12 Inches above grade |
| - John Core | | | | 100 | | 15. Well grouted? | K Bentonite Concrete |
| | | | | | | Depth: From O ft. to | 10 ft. |
| RROCK 54' | | | | | | | e contamination: Oil Well |
| 31 | | | | | | Well disinfected upon comple | etion? Yes X No. I |
| 23' sat thick | | | | | | | stern Land Roller |
| 14 Alluvium | | | | | | Model number 3-8AH Length of drop pipe 50 | HP10 Volts_ <u>480</u> |
| | | | | | | Type: Submersible | X Turbine |
| | | | | \vdash | | Jet | Reciprocating |
| (Use a second sheet if needed) | | | | | | Centrifugal | Other N |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's This well was drilled under m | ny jurisdiction and this report |
| | | | | | is true to the best of my know | wledge and belief. | |
| Topography: 2305 | | | | | Woofter Drilling, Inc | | lng, Inc, 343 |
| Topography: Hill Slope Z 305 | | | | | | Business name Address HWV 4 560 | Dodge City KS |
| X 11 in 1 | | | | | | Address History | Doll 9/6/ |
| Valley | 70PO 72 | <i></i> | | | | Signed Authorized rep | presentative |