

1 LOCATION OF WATER WELL: McPherson	FRACTION SW 1/4 SW 1/4 SW 1/4	Section Number 13	Township Number T 21 S	Range Number R 3W E/W
Distance and direction from nearest town or city street address of well if located within city? 4 miles West & 1 mile North of Moundridge, Kansas				
2 WATER WELL OWNER: FLICKNER, Galen RR#, ST. ADDRESS, BOX #: R.R. #1 CITY, STATE, ZIP CODE: Moundridge, Kansas		Board of Agriculture, Division of Water Resource Application Number: 40.699		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 112 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL 38 FT. BELOW LAND SURFACE MEASURED ON 06/07/1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 800 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 112 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
	5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass SDR-26 Threaded Blank casing Diameter 16 in. to 72 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 19.75 lbs. / ft. Wall thickness or gauge No. .616 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
	SCREEN-PERFORATION INTERVALS: from pvc. 72 ft. to 92 ft., From ft. to ft. GRAVEL PACK INTERVALS: from galv. 92 ft. to 112 ft., From ft. to ft. from ft. to ft., From ft. to ft.			
	6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite & cement Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS		
0	2	soil		
2	10	brown clay		
10	20	tan clay		
20	35	tan & yellow clay		
35	43	sandy tan clay		
43	65	very fine to coarse sand & fine gravel, silty		
65	72	very fine to coarse sand, very silty		
72	112	fine to coarse sand & fine to medium gravel, medium loose		
112	114	black shale		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/07/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/13/95 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>				