


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: McPherson Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 36 Township Number: T 21 S Range Number: R 3 W

Distance and direction from nearest town or city street address of well if located within city? 4 miles west & 1 mile south of Moundridge, KS.

2 WATER WELL OWNER: MARK VOIGTS RR#, St. Address, Box #: 807 S. CHRISTIAN AVE. City, State, ZIP Code: MOUNDRIDGE, KS. 67107 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 

4 DEPTH OF COMPLETED WELL: 92 ft. ELEVATION: 9-7-84 ft. Depth(s) Groundwater Encountered 1. 92 ft. 2. 92 ft. 3. 92 ft. WELL'S STATIC WATER LEVEL 92 ft. below land surface measured on mo/day/yr 9-7-84 Pump test data: Well water was 20 gpm: Well water was 92 ft. after 92 hours pumping 92 gpm Est. Yield 20 gpm: Well water was 92 ft. after 92 hours pumping 92 gpm Bore Hole Diameter 8 in. to 92 ft., and 92 in. to 92 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓ If yes, mo/day/yr sample was submitted 9-7-84 Water Well Disinfected? Yes ✓ No ✓

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped ✓ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ✓ Threaded ✓ Blank casing diameter 5 in. to 82 ft., Dia 5 in. to 82 ft., Dia 5 in. to 82 ft. Casing height above land surface 12 in., weight 2.91 lbs./ft. Wall thickness or gauge No. 265 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 7 PVC 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 PVC SCREEN-PERFORATED INTERVALS: From 82 ft. to 92 ft., From 82 ft. to 92 ft., From 82 ft. to 92 ft., From 82 ft. to 92 ft., GRAVEL PACK INTERVALS: From 15 ft. to 92 ft., From 15 ft. to 92 ft., From 15 ft. to 92 ft., From 15 ft. to 92 ft.,

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5 ft. to 15 ft., From 5 ft. to 15 ft., From 5 ft. to 15 ft., From 5 ft. to 15 ft., What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage How many feet? 100 ft Direction from well? South

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-9-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 10-7-84 under the business name of PETERSON IRRIGATION, INC. by (signature) Mike Peterson

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.