


1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 NE 1/4 Section Number 2 Township Number T 21 S Range Number R 33 (E/W)
 County: Finney

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Kevin Brungardt
 RR#, St. Address, Box # : 1603-1/2 St. John St. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Garden City, KS 67846 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 163 ft. ELEVATION: ft.

 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 106 ft. below land surface measured on mo/day/yr 11-17-05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 26 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 163 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface 12 in., weight lbs./ft. Wall thickness or guage No. 200 PSI
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 123 ft. to 163 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 163 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other
 Grout Intervals: From 5 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	60	brown clay			
60	73	brown clay, fine sand streaks			
73	80	fine to medium sand			
80	83	light brown clay			
83	103	fine sand, brown clay streaks			
103	124	brown clay + gypsum			
124	130	med. to coarse sand, small gravel			
130	138	med. to coarse sand, brown clay streaks			
138	142	brown clay			
142	158	med. to coarse sand, clay streaks			
158	161	med. to coarse sand, small gravel			
161	163	yellow shale			
163		black shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 11-17-05 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's Licence No 532 This Water Well Record was completed on (mo/day/yr) 12-19-05
 under the business name of Midwest Well + Pump Inc. by (signature) Victor Surkup