WATER WELL RECORD			Form W	WC-5	Di	Division of Water Resources App. No.				
1 LOCATION OF WATER WELL:			Fraction		1	on Number		Range Number		
County: Finney			1/4 NE 1/4 NE			32 T 21 S R 33 DE 🗸				
	Street/Rural Address of Well Location; if unknown, distance & direction						Global Positioning System (GPS) information:			
from	from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)				
Big	Big Lowe Rd. & Gano Rd go 2314' East and 315' South					Longitude: (in decimal degrees)				
						Elevation:				
2 WATER WELL OWNER: Steven Krehbiel						Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:				
RR#, Street Address, Box #: 5515 W. Gano Rd.						GPS unit (Make/Model:)				
City, State, ZIP Code : Holcomb KS, 67851					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey					
	, ,	Holcomi	J N3, 07031				3 m, 🔲 3-5 m, 🔲			
3 LOCATE WELL										
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 122 ft.									
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1)									
	WELL STATIC WATER ELVEL									
1 1	Pump test data: Well water was .112ft. after .5									
	EST. YIELD. 102gpm. Well water wasft. after									
W ELL WATER TO BE USED AS: Public water supply Geothermal Injection well										
	Domostio Decodlet Doil field water sweets Downton Downton Downton									
SW SE Dolliestic Feedlot On field water supply Dewatering Other (specify below)										
Was a chemical/bacteriological sample submitted to Department? Yes No										
	S If yes, mo/day/yr sample was submitted									
was submitted: Water well disinfected?										
CASING JOINTS: Glued Clamped Welded Threaded										
Casing diameter .10 in. to .102 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface .12 in., Weight 200lbs./ft., Wall thickness or gauge NoSDR21										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)										
Brass Galvanized Steel None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)										
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
From										
GRAVEL PACK INTERVALS: From										
From										
Grout Intervals: From .0										
What is the nearest source of possible contamination:										
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)										
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☑ Abandoned water well										
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well										
		n well North						•••••		
FROM	TO	LITHOLOG	C LOG	FROM	TO		OG (cont.) <u>or</u> PLU	GGING INTERVALS		
0	2	Top Soil		100		Gravel				
2	22	Brown Sticky Clay		120	122	Yellow Soa	p Stone			
22	42	Gypsum With Hard Stre								
42	56	Brown Clay With Gypsu								
56	68	Medium to Coarse Sand								
		Small Gravel, Few Sma	II Brown Clay							
00	74	Streaks Brown Clay With Medium to Coarse								
68	74		ii to Coarse							
74	100	Sand Streaks	J M/AL C "							
74	120	Medium to Coarse Sand		T 777 '						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged										
under my jurisdiction and was completed on (mo/day/year) .6.9.16										
Kansas Water Well Contractor's License No. 532 This Water Well Record was completed on (mo/day/year) 6-24-16										
under the business name ofMidwest Well & Pump Inc										
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Toneka Kansas 66612-1367										
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at										
http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy										