WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 2WSedgwick \mathbf{SW} NW13 Т 22 1/4 1/4 S E/W Distance and direction from nearest town or city street address of well if located within city? 8704 W. Conrey Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W. York ZIP CODE: 67215 Wichita, Kansas CITY, STATE: Application Number 60 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/2/14 Pump test data Well water was ft. after hours of pumping @ NEapm ΝW Mile Est. Yield: Well water was ft. after hours of pumping @ apm gpm Bore Hole Diameter 12 in. to **60** and ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only S₩ SE 3. Feedlot 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? NO submitted Was Water Well Disinfected? YES TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: C Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 40 Dia. Dia. to in. ft. to 12 Weight: 2.35 Casing height above land surface: in lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 9. ABS 1. Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 40 60 ft. From to ft. ft. From to ft.. From ft. ft. to 24 **GRAVEL PACK INTERVALS:** ft. From to 60 ft., From to ft. ft. From ft From ft. ft GROUT MATERIALS: Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft., From ft. to ft., From ft What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit North How many feet? 10 ft. plus Direction from well? From Τо LITHOLOGIC LOG From LITHOLOGIC LOG To topsoil clay 15 35 fine sand 35 45 clay 45 medium sand 60

Contractor's or Landowner's Certification: This water well was 1.

Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/2/2014 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/4/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp

County: Sedawick Fraction SE NE NW	Sec <u>34</u> T_ <u>26</u> _S_R/EW
CORRECTION(S) TO WATER WELL COMP (to rectify lacking or incorrect in the construction)	,
Location was listed as:	Location changed to:
Section-Township-Range: 13 - 22 5 - 2 W Fraction (1/4 1/4 1/4):	34-265-1W
Fraction (1/4 1/4 1/4): NW SW NW	SE NE NW
Other changes: Initial statements:	
Changed to:	
Comments:	
Verification method: <u>Wellsite</u> address, cit	y street map, and
Verification method: Wellsite address, city mapping tool on KGS webs	initials: OP Ldate: 12/1/2014
Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Cor	
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.	