

1) LOCATION OF WATER WELL: County: McPherson		Fraction SE ¼ SE ¼ SE ¼ SE	Section Number 8	Township Number T 21 S	Range Number R 4 E/W
Distance and direction from nearest town or city street address of well if located within city? In city limits of Inman, KS					
2) WATER WELL OWNER: Mid-Kansas Coop As. RR#, St. Address, Box # : 81 Bypass City, State, ZIP Code : McPherson, KS 67460					
Board of Agriculture, Division of Water Resources Application Number:					
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N - - NW - - NE - - W E - - SW - - SE - - S X		4) DEPTH OF COMPLETED WELL 29.0 ft. ELEVATION: 08-20-05 ft.			
		Depth(s) Groundwater Encountered 1 2 3 ft. below land surface measured on mo/day/yr WELL'S STATIC WATER LEVEL 12.2 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes No X			
5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 7 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface -2 in., weight SCH40 lbs./ft. Wall thickness or guage No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 29 ft. to 9 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 29 ft. to 6 ft., From ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 6 ft. to 2 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? East How many feet? 65					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Topsoil	6	2	Bentonite
5	10	Dark brown clay	2	-2	Cement
10	20	Grey to light grey clay			
20	25	Tan/grey clay with caliche			
25	30	Tan clay to red clay			
					MW-4
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-19-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 665 This Water Well Record was completed on (mo/day/year) 09-19-05 under the business name of Pratt Well Environmental by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					