

1 LOCATION OF WATER WELL: County: McPherson		Fraction SE 1/4 SE 1/4 SE 1/4 SE		Section Number 8	Township Number T 21 S	Range Number R 4 E
Distance and direction from nearest town or city street address of well if located within city? In city limits of Inman, KS						
2 WATER WELL OWNER: Mid-Kansas Coop As. RR#, St. Address, Box # : 81 Bypass City, State, ZIP Code : McPherson, KS 67460 Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div><div><div>N</div><div>W</div><div>E</div><div>S</div><div>SW</div><div>SE</div><div>NW</div><div>NE</div><div>X</div></div></div>		4 DEPTH OF COMPLETED WELL 29.48 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 12.65 ft. below land surface measured on mo/day/yr 08-30-05 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 9.48 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface -2 in., weight SCH40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 29.48 ft. to 9.48 ft. From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft. From 29.48 ft. to 7.5 ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 7.5 ft. to 1.5 ft. From ft. to ft. to ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Northwest How many feet? 4						
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS				
0	5	Topsoil	9.48 1.5 Bentonite			
5	25	Light tan clay	1.5 .2 Cement			
25	30	Light tan to red shale				
MW-6						