

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number				
County: McPherson		SW ¼ SW ¼ NW ¼	29	T 21 S	R 4 E				
Distance and direction from nearest town or city street address of well if located within city? 2 mi. S, 1 W & S of Inman									
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		John Herron Rt 1 Inman, KS 67546							
		Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 50 ft.							
N <table border="1" style="margin:auto; width:150px; height:150px;"><tr><td>NW</td><td>NE</td></tr><tr><td>X SW</td><td>SE</td></tr></table> S		NW	NE	X SW	SE	ELEVATION:			
		NW	NE						
		X SW	SE						
		Depth(s) Groundwater Encountered 1.....ft. 2.....ft. 3.....ft. WELL'S STATIC WATER LEVEL ... 10 ft. below land surface measured on mo/day/yr . 12-11-87 Pump test data: Well water was 48 ft. after 5 hours pumping 10 gpm Est. Yield ... 10 gpm: Well water wasft. afterhours pumpinggpm Bore Hole Diameter... 10 in. to 54 ft., and.....in. toft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.. X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Welded							
② PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Threaded							
Blank casing diameter 6 in. to 30 ft., Dia.....in. toft., Dia.....in. toft.									
Casing height above land surface.... 12 in., weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		③ PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped ⑤ Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From..... 30 ft. to 50 ft., From.....ft. toft.									
GRAVEL PACK INTERVALS: From..... 25 ft. to 54 ft., From.....ft. toft.									
6 GROUT MATERIAL: ① Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From..... 3 ft. to 13 ft., From.....ft. toft., From.....ft. toft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank ④ Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? S		How many feet? 80							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	30	Bk clay							
30	50	clay & clay silt							
50	54	Bk clay							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-11-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 6-27-88 under the business name of Miller Drilling by signature [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									