


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County <u>Mcpherson</u>	Township name <u>superior</u>	Fraction <u>NW 1/4 / NE 1/4</u>	Section number <u>36</u>	Town number <u>2</u> <u>T-2-S</u>	Range number <u>R-4-W</u>
Distance and direction from nearest town or city: <u>7 miles SE of Inman</u>				3 Owner of well: <u>ALBERT ENNAS</u>		
Street address of well location if in city:				Address: <u>RR #1 INMAN</u>		
Locate with "X" in section below: 				Sketch map: 		
2				4 Well depth: <u>100'</u> ft. Date of completion <u>4/4/25</u> Well diameter <u>4"</u> in.		
Type and color of material				5 ☐ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
From To				6 Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well ☐		
<u>Loam</u> 0 5				7 Casing: Material <u>PVC</u> Height: <u>above</u> below Threaded ☐ Welded ☒ Surface <u>12</u> in. Diam. <u>6"</u> Weight <u>3.22</u> lbs./ft. <u>12"</u> in. to <u>100</u> ft. depth Drive shoe? ☐ Yes ☒ No		
<u>" to brown clay</u> 5 10				8 Screen: Manufacturer <u>Cert-Teed</u> Type <u>PVC</u> Dia. <u>6"</u> Slot/gauze <u>0.46</u> Length <u>20'</u> Set between <u>96</u> ft. and <u>76</u> ft. Fittings: <u>1/8" to 1/2"</u> Gravel pack ☒ Yes ☐ No Size range of material <u> </u>		
<u>" " Sandy</u> 10 15				9 Static water level: <u>42</u> ft. below land surface Date <u>4/4/25</u>		
<u>brown to grey clay</u> 15 20				10 Pumping level below land surfaces: <u>45</u> ft. after <u>1</u> hrs. pumping <u>15</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>150</u> g.p.m.		
<u>Sandy clay</u> 20 45				11 Water sample submitted: ☐ Yes ☒ No Date <u> </u>		
<u>grey clay</u> 45 74				12 Well head completion: ☒ Pitless adapter ☐ Inches above grade		
<u>Sandy clay</u> 74 80				13 Well grouted? ☒ Yes ☐ No ☒ Neat cement ☒ Bentonite ☐ <u> </u> Depth: From <u>15</u> ft. to <u>3</u> ft.		
<u>Sand - med to coarse</u> 80 100				14 Nearest source of possible contamination: <u>house</u> ft. <u>105</u> Direction <u>SE</u> Type <u>sewer</u> Well disinfected upon completion? ☒ Yes ☐ No		
<u>compacted</u>				15 Pump: ☐ Not installed Manufacturer's name <u>Valley</u> Model number <u>1250</u> HP <u>1/2</u> Volts <u>230</u> Length of drop pipe <u>80</u> ft. capacity <u>15</u> g.m.p. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
<u>clay - grey</u> 100' -				16 Remarks: elevation		
(use a second sheet if needed)				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>PAULS INC. #175</u> Business name License No. Address <u>Box 26, Heaton</u> Signed <u>Paul B. Pauls</u> Date <u>4/4/25</u> Authorized representative		

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:		County McPherson	Township name Superior	Fraction N 1/4 / N 1/4	Section number 36	Town number T-2-S	Range number R-4-W
Distance and direction from nearest town or city: 7 Mile SE-Inman				3 Owner of well: Albert ENNS			
Street address of well location if in city:				Address: RR #1 INMAN			
Locate with "X" in section below: N W E S 1 Mile		Sketch map: ALBERT ENNS		4 Well depth: 120' ft. Date of completion 4/4/25 Well diameter 6" in. 14" bore hole			
2 Type and color of material		From		To		5 ☐ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
		0-5		5		6 Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well ☐	
		5-10		10		7 Casings: Material PVC Height: above below Threaded ☐ Welded ☐ Surface 12 in. Diam. 12 in. to 100 ft. depth Drive shoe? ☐ Yes ☐ No in. to in. ft. depth	
		10-15		15		8 Screen: Pipe zone Cent-tee Manufacturer PAUL'S INC Type PVC Dia. 6" Slot/gauze 1/8" Length 20' Set between 96 ft. and 72 ft. Fittings: Gravel pack ☒ Yes ☐ No Size range of material #8	
		15-20		20		9 Static water level: 42 ft. below land surface Date 4/4/25	
20-65		20		65		10 Pumping level below land surfaces: 45 ft. after 1 hrs. pumping 15 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 169 g.p.m.	
65-74		65		74		11 Water sample submitted: DID ANALY FTS ☐ Yes ☒ No Date Available	
74-80		74		80		12 Well head completion: ☒ Pitless adapter ☐ Inches above grade	
80-81		80		81		13 Well grouted? ☒ Yes ☐ No ☒ Neat cement ☐ Bentonite ☐ Depth: From 15 ft. to 3 ft.	
81-100		81		100		14 Nearest source of possible contamination: ft. 105' Direction SE Type S Well disinfected upon completion? ☐ Yes ☒ No	
100'-						15 Pump: ☒ Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.m.p. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
16 Remarks: elevation						17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. PAUL'S INC #175 Business name _____ License No. _____ Address Box 26 HESSTON Signed Paul Paulson Date 4/8/25 Authorized representative	