WATER WELL RECORD	Form W	WC-5	Di	ivision of Wate	r Resources App. N	o	
1 LOCATION OF WATER WELL:	Fraction					Range Number	
County: McPherson	145E 145E	= 45E 1	4	24	T 2 / S	R 4 □E 🗷 W	
Street/Rural Address of Well Location; if unknown, distance & o					System (GPS) ir		
from nearest town or intersection: If at owner's address, check						(in decimal degrees)	
			Long	Longitude: (in decimal degrees)			
			Eleva	Elevation:			
2 WATER WELL OWNER: / a pen Postien					4, 🔲 NAD 83, 🗀	NAD 27	
Luren				Collection Method:			
RR#, Street Address, Box #: 209 12 5 Aue			☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
Inman, KS 67546				Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
3 LOCATE WELL	1000	, , , ,	Lot. 1	recuracy.	э m, 🔲 э-э m, 🗀	, 5-15 m, > 15 m	
WITH AN "X" IN 4 DEPTH OF	COMPLETED WEL	L <i>l.9</i> .	سي	ft.			
SECTION BOX: Depth(s) Groun	Depth(s) Groundwater Encountered (1)						
N WELL'S STA	Depth(s) Groundwater Encountered (1)						
Pum	Pump test data: Well water was						
EST. YIELD	EST. YIELDgpm. Well water wasft. after hours pumpinggpm						
W E Bore Hole Dian	Bore Hole Diameter						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SW SE Domestic							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected? Yes □ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
□ Louvered shutter □ Key punched □ Wire wrapped 🛣 Saw cut □ Other (specify)							
From							
GRAVEL PACK INTERVALS: From 23 ft. to 143 ft., From ft. to ft.							
From							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other							
Grout Intervals: From							
What is the nearest source of possible contamination:							
Septic tank							
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well							
Direction from well				ell			
FROM TO LITHOLO	JIC LOG	FROM	TO			IGGING INTERVALS	
26 38 Tan F-M 50		148	165		and - Ver	y Rocky	
		165	/72	Sand		1 <i>j</i> -	
	nd	172	192		nd	***************************************	
52 62 Gr Clay		192	200	ROCKY	Br Cluy		
	5.4/	200	2/2	Grey	Shale '		
	nd						
	and						
	nd-Sm layers	Clay					
129 143 4 C Sas							
143 148 Rocky Br Cl							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year)							
Kansas Water Well Contractor's License No							
under the business name of Miller Drilling by (signature) by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WA	TER WELL OWNER and i	retain one for	your recor	rds. Include fee	of \$5.00 for each c	onstructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							