NW-14M

WATER WELL RECOR	RD For	m WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER County: McPherson		L SWY NWY	Section Number Township No. Range Number T 21 S R 4 DE 8
Street/Rural Address of We from nearest town or inters	ell Location; if unknown, dist. ection: If at owner's address, 19 ton Road + Sout	ance & direction check here .	Global Positioning System (GPS) information: Latitude: 38.22,123 (in decimal degree Longitude: 97.77555 (in decimal degree Elevation:
2 WATER WELL OWNER: USDA - Steuc Gilmore RR#, Street Address, Box #: Stop OSI3 Room 4714-5 City, State, ZIP Code: 1400 Independence Auc, SW			Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method: ☐ GPS unit (Make/Model:
City, State, 217 Code	Joshington, DC. 2025	0-05/3	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Surve Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
WITH AN "X" IN 4 D SECTION BOX: Dep	LL'S STATIC WATER LEV	red (1) ft. 1	ft. (2) ft. (3) ft. (5) ft. (2) ft. (1) ft. (2) ft. (2) ft. (3) ft. (4) ft. (5) ft. (6) ft. (7) ft. after ft. (7) ft. after ft. (7) ft. after ft. (7) ft. (8)
w EST	NYIELDgpm. Well e Hole Diameter 8in	water was ft.	ft. after hours pumping gpr, and hours pumping hours ft. supply Geothermal Injection well
Was	Irrigation Industrial sa chemical/bacteriological sa	Domestic-lawn	supply ☐ Dewatering ☐ Other (Specify below n & garden 🔀 Monitoring well Department? ☐ Yes 🔀 No
S Wat	If yes, mo/day/yr sample wa er well disinfected? Yes		
5 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 1.5 in. to 8.5 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 1.5 in., Weight 93 lbs./ft., Wall thickness or gauge No. 5.4.86			
TYPE OF SCREEN OR PERFORATION MATERIAL Steel Stainless Steel PVC Other (Specify)			
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:			
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify) SCREEN-PERFORATED INTERVALS: From			
From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 8.3 ft. to 9.5 ft., From ft. to ft.			
From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other			
Grout Intervals: From 2:	5 ft. to 8.3 ft., F	rom ft.	to ft., From ft. to ft
What is the nearest source of po-			
Sewer lines	☐ Lateral lines ☐ Pit privy☐ ☐ Cesspool ☐ Sewage (ago)☐ ☐ Seepage pit ☑ Feedyard		s
Direction from well			m well
	ITHOLOGIC LOG		O LITHO. LOG (cont.) or PLUGGING INTERVAL
0 40 Clay			
40 95 Wedthe	red Shalt		
	•		
	1		
LOONING CONTROL OF THE	OUNTED OF STREET	1011	, , , , , , , , , , , , , , , , , , , ,
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year). 3/23// and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 5.9.7. This Water Well Record was completed on (mo/day/year)			
			y (signature) Zem Miller
NSTRUCTIONS: Use typewriter or ba white, blue, pink) to Kansas Departmen	ll point pen. PLEASE PRESS FIRM t of Health and Environment, Bure	ALY and <u>PRINT</u> clearly. To of Water, Geology S	Please fill in blanks and check the correct answers. Send three copie ection, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367 ecords. Include fee of \$5.00 for each constructed well. Visit us a
tp://www.kdheks.gov/waterwell/index.ht			Charles White Conv. Plus Conv. Pink Conv