MW-1651

WATER WELL REC	CORD	Form	WWC-5	Division of Wate	er Resources App. N	
1 LOCATION OF WA				Section Number		Range Number
County: McPhers	501	1/2 SW1/4 /	VEY SEY	17	T 21 S	R 4 □E XW
Street/Rural Address o	f Well Location: if	unknown distanc	e & direction	Global Positioning		oformation:
from nearest town or in				Latitude: 38.	22235	(in decimal degrees)
Corner of field off 8th Ave			other	Longitude: 97	78036	nformation: (in decimal degrees) (in decimal degrees)
Bolzer Drive			•	Elevation:		
		C1		Datum: WGS 8	4, 🗌 NAD 83, 🔲	NAD 27
2 WATER WELL OWNER: USDA - Steve			4C 41-5	Collection Method:		
RR#, Street Address, Box #: 5top 0513 Room City, State, ZIP Code : 1400 Independen			ve sw	GPS unit (Make/Model:) Digital Map/Photo, Topographic Map, Land Survey		
City, State, ZIP Code	1400 +10	0 - 20250	0512			
3 LOCATE WELL	Woshington,	DC. 20250	-03/3	Est. Accuracy:		2-12 m'
WITH AN "X" IN	4 DEPTH OF C	OMPLETED WE	II. 35	., ft.		
SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2)						
WELL'S STATIC WATER LEVEL 17.06. ft. below land surface measured on mo/day/yr. 9/15///						
						oing gpm
	EST. YIELD	gom. Well wa	ter was	ft. after	hours pum	oing gpm
W	Bore Hole Diamet	er 8 in. to	3.5	t., andin.	to	ft.
				er supply 🔲 Ge		
						ther (Specify below)
	☐ Irrigation . [☐ Industrial ☐	Domestic-lay	vn & garden 🔀 Mo	nitoring well	
	Was a chemical/ba	acteriological samp	le submitted to	Department?	Yes 🕱 No	
S If yes, mo/day/yr sample was submitted						
mile	Water well disinfe	cted? 🗌 Yes 🕱	No			
5 TYPE OF CASING US	SED: Steel	₩ PVC □	Other			
5 TYPE OF CASING USED: Steel PVC Other						
Casing diameter						
Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL.						
☐ Steel ☐ Stainless Steel 🔀 PVC ☐ Other (Specify)						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 25, ft. to 3.5 ft., From ft. to ft.						
SCREEN-PERFORATED	INTERVALS: FR	om 2-9	n. to	π., From	п. то) II.
CRAVICE DACK!	FI DVALO. E-	om 7 3	π. το	T., From	It. to) ft.) ft.
GRAVELPACK				ft., From		
6 GROUT MATERIAL:				te Other		
	2.5 ft to	23 ft From	n Bentoni	to ft., l	From	ft to ft
					TOTAL	10.10
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagdon Fuel storage Abandoned water well						
Watertight sewer lines	s - Seepage pit	➤ Feedyard	🔀 Fertilizer sto			
Direction from well			. Distance fr	om well		
FROM TO	LITHOLOGIC	LOG	FROM	TO LITHO LO	G (cont.) or PLUG	GING INTERVALS
0 35 6/9	У					
		1.				
		1.5				
		10 P. J				
	1					
CONTRACTOR'S OR LA	ANDOWNER'S	ERTIFICATION	V: This water	vell was 🔀 construct	ed Treconstruct	ed or I plugged
inder my jurisdiction and was						
Cansas Water Well Contracto		Thie W	ater Well Rec	ord was completed or	i (mo/day/vear)	9721111
nder the business name of .	Boall Long	4001 COM	POAY	by (signature).	, (morday) year)	
NSTRUCTIONS: Use typewriter		ASE PRESS FIRMLY	and PRINT clearly	Please fill in blanks an	d check the correct an	swers. Send three conies
vhite, blue, pink) to Kansas Depar						
-1 206 206 6622 C1						
	e copy to WATER W			records. Include fee of		
tp://www.kdheks.gov/waterwell/ind	e copy to WATER W				\$5.00 for each const	ructed well. Visit us at