MW-205

WATER WELL REC	CORD	Form W	WC-5	Div	vision of Water	r Resources App. N	o	
1 LOCATION OF WA		Fraction			n Number		Range Number	
County: Me Pher	son	14 NE 14 NE	= 14N = 1/4	CLI	2 <i>0</i>	T 2/ S	R # □E ∑ W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here								
South of Buckskin Road 350' west of					Global Positioning System (GPS) information: Latitude: 38, 2173 (in decimal degrees) Longitude: 97, 7770.8 (in decimal degrees)			
8th Ave.					Elevation:			
2 WATER WELL OWNER: USDA -Steve Gilmore					Datum: WGS 84, NAD 83, NAD 27			
RR#, Street Address, Box #: 5100 0513 Room 4714-5					Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code 1400 Independence Ave SW					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Washington D.C. 20250-0513					Est. Accuracy:			
3 LOCATE WELL WITH AN "X" IN	4 DEPTH OF	COMPLETED WEL	_L 4	0	ft.			
SECTION BOX:								
N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr								
Pump test data: Well water was								
WNW NE E EST. YIELDgpm. Well water wasft. after hours pumpinggpm Bore Hole Diameter								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
Domestic Deedlot Oil field water supply Dewatering Other (Specify below)								
│								
Was a chemical/bacteriological sample submitted to Department? Yes No								
S If yes, mo/day/yr sample was submitted								
Water went distincted: 1 Tes La 140								
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other								
Casing diameter in, to								
Casing diameter in. to 30 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight 193 lbs./ft., Wall thickness or gauge No. 324 80								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter								
SCREEN-PERFORATED INTERVALS: From 3.0 ft. to 4.0 ft., From ft. to ft.								
From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
		•	n	ft. to	ft.,	From	ft. toft.	
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						(creaty total)		
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Direction from well ☐ Distance from Well								
FROM TO	LITHOLOG		FROM	TO WE			JGGING INTERVALS	
0 38 01	ay		110171		2.1110. 1	o (com.) or 1 De	JOHN SHIPKING	
38 40 Wes	athered.	Shale						
A COMED A CECUTA CO	D T A STEAM OF THE	10 Opposes America	NI. TI.:	11				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🖫 constructed, \Box reconstructed, or \Box plugged under my jurisdiction and was completed on (mo/day/year) 9.1/3.1.1 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No								
under the business name of . Doart Lorgyear . Company by (signature)								
INSTRUCTIONS: Use typew	vriter or ball point per	. PLEASE PRESS FIRML	Y and PRINT cle	arly. Ple	ase fill in blanks	and check the correct		
(white, blue, pink) to Kansas I Telephone 785-296-5524. Ser	nd one copy to WAT							
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212						<u> </u>	001303	