WATER WELL	RECORD	Form W	WC-5	Division of Wat	er Resources App. N	Io.	
	F WATER WELL:	Fraction	N/ 1/ NNA/ 1/	Section Number	Township No.	Range Number	
County: McPherson 1/4 SW 1/4 SW 1/4 NW 1/4 Street/Rural Address of Well Location; if unknown, distance & direction				···	T 21 S	R 4 E W	
	owner's address, chec	Global Positioning System (GPS) information: Latitude: .38.22580009 (in decimal degrees)					
NE from intersection of South Main Street and Farmington Road. MW05.				Longitude: 97.77539066 (in decimal degrees) Elevation: 1525.601			
2 WATER WELL OWNER: USDA - S. Gilmore - 0513, 4714-S				Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 1400 Independence Ave. SW City, State, ZIP Code : Washington DC 20250.0513				☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, 【 Land Survey			
Wastington, DO 20230-0313				Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 45							
	SECTION BOX: Depth(s) Groundwater Encountered (1)						
N	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr. 2/16/2011						
Pump test data: Well water was							
W $ X $ Bore Hole Diameter 3.25 in. to .45 ft., and in. to ft.							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
SWSE Domestic							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No							
S If yes, mo/day/yr sample was submitted							
5 TYPE OF CASING USED: Steel V PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .1							
Casing height above land surface0.5 in., Weight 0.33 lbs./ft., Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
Louvered shutter Key punched Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From							
From the first fit to the fit							
GRAVEL PACK INTERVALS: From . 33 ft. to . 45 ft., From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Flush mount							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Flush mount Grout Intervals: From 3.0 ft. to 31 ft., From 31 ft., From 3 ft., From 3 ft. to 0.5 in. ft.							
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well							
FROM TO	LITHOLOG		FROM			JGGING INTERVALS	
	Clayey silt to silty clay Veathered red and gre	an chala	-				
30 43 (reamered red and gre	en snale					
			-				
	The state of the s						
ļ			-				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .11/7/2009 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 680 This Water Well Record was completed on (no/dax/year) 10/08/2012 under the business name ofDelta Environmental by (signature)1							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 620 Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at							
http://www.kdheks.gov/waterwell/index.html.							
120/2 024-1212				Check: 🔲 W	ппе сору, 🔲 Ві	ue Copy, 🔲 Pink Copy	