WATER WELL REC	CORD	Form W	WC-5	Di	vision of Wate	er Resources App. N	10. L		
1 LOCATION OF WATER WELL:		Fraction 1/4 SW 1/4 SW		Section	on Number 16	Township No.	Range N		
	if unknown, distance &	own, distance & direction Global Positioning System (GPS) information				nformation:			
from nearest town or intersection: If at owner's address, check here .				Latitude: .38.22452575 (in decimal degrees)					
NE from intersection of South Main Street and Farmington Road. MW07.				Longitude: 97.77493513 (in decimal degrees) Elevation: 1524.315					
2 WATER WELL OWNER: USDA - S. Gilmore - 0513, 4714-S					Datum: WGS 84, NAD 83, NAD 27 Collection Method:				
RR#, Street Address, Box #: 1400 Independence Ave. SW				П	GPS unit (Make/Model:				
City, State, ZIP Code : Washington, DC 20250-0513				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m					
3 LOCATE WELL	4 DEPTH OF	COMOLETED WELL	т 41.5		fr				
WITH AN "X" IN SECTION BOX:	AN "X" IN 4 DEPTH OF COMPLETED WELL 41.5 ft. Depth(s) Groundwater Encountered (1) ft. (2) ft. (3)								
N	WELL'S STATIC WATER LEVEL 26.58 ft. below land surface measured on mo/day/yr. 2/16/2011								
Pump test data: Well water wasft. after								gpm	
WNW									
Was a chemical/bacteriological sample submitted to Department? Yes V No									
S If yes, mo/day/yr sample was submitted									
1 mile Water well disinfected? ☐ Yes ☑ No									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 1 in. to 41.5 ft., Diameter in. to ft., Diameter ft., Diameter ft., Diameter ft.									
Casing height above land surface									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ✔ PVC ☐ Other (Specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot									
SCREEN-PERFORATED INTERVALS: From 31.5 ft. to 41.5 ft. From ft. to ft.									
From									
GRAVEL PACK INTERVALS: From. 29.5 ft. to .41.5 ft., From ft. to									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Flush mount									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Flush mount Grout Intervals: From 3.0 ft. to 27.5 ft., From 27.5 ft. to 29.5 ft., From 3 ft. to 0.5 in. ft.									
What is the nearest source of possible contamination:									
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well									
☐ Watertight sewer I Direction from well			Fertilizer st		Oil well/g	as well			
FROM TO	LITHOLOG		FROM	TO TO		OG (cont.) or PL	UGGING	INTERVALS	
0 36 Silt/cla							,		
	ered shale (base	ed on CPT						·····	
electro	nic readings)		-						
								-	
			-						
		,						**************************************	
	·····								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .11/8/2010 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 680 This Water Well Record was completed on (mo/day/year) 10/08/2012									
under the business name of Delta Environmental by (signature). INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and cheek the entret answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.									
(white, blue, pink) to Kansas I Telephone 785-296-5524. Ser	Depar tment of Health	and E nvironment, Bureau TER WELL OWNER and	of Water, Geol- retain one for	ogy Secti zour reco	on, 1000 SW Ja rds. Include fe	ackson St., Synte 420 ee of \$5.00 for each	/ I opeka, Ka constructed	unsas 666 12-1367. well. Vi sit us at	
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212				C	heck: 🔲 W	nite Copy, 🔲 B	iue Copy,	☐ Pink Copy	