WATE	R WEI	LL RECORD	Form W	WC-5	Di	vision of Wate	r Resources App. N	o. L		
1 LOCATION OF WATER WELL:			Fraction		Section	on Number	Township No.	Range N		
County: McPherson			1/4 SE 1/4 SE	E 1/4 NE 1/4	1	17	T 21 S	R 4	□E ☑ W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here									imal degrees)	
NW from intersection of South Main Street and Farmington Road.						Longitude: 97.77585099 (in decimal degrees)				
MW09.					Eleva	Elevation: 1525.583 Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: USDA - S. Gilmore - 0513, 4714-S						Collection Method:				
RR#, Street Address, Box #: 1400 Independence Ave. SW City, State, ZIP Code : Washington, DC 20250-0513						☐ GPS unit (Make/Model:				
Washington, DO 20200-0010						Est. Accuracy:				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 39.5 ft.										
1	SECTION BOX: Depth(s) Groundwater Encountered (1)									
	WELL'S STATIC WATER LEVEL .27.27ft. below land surface measured on mo/day/yr. 2/16/2011									
Pump test data: Well water was ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm										
Per Hole Diameter 3 25 in to 39.5 ft and in to ft								gpm		
WELL WATER TO BE USED AS: □ Public water supply □ Geothermal □ Injection well										
SWSE Domestic										
Was a chemical/bacteriological sample submitted to Department? Yes V No										
S If yes, mo/day/yr sample was submitted										
1 mile Water well disinfected? ☐ Yes ☑ No										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 1 in. to 39.5 ft., Diameter in. to ft., Diameter ft.										
Casing diameter										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 29.5 ft. to 39.5 ft., From ft. to ft.										
From										
GRAVEL PACK INTERVALS: From										
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Flush mount										
Grout Intervals: From 3.0 ft. to 25.5 ft., From 25.5 ft. to 27.5 ft., From 3 ft. to 0.5 in. ft.										
What is the nearest source of possible contamination:										
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below) Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well									below)	
	Watertig	ht sewer lines	pit 🔽 Feedyard	Fertilizer s	torage	Oil well/ga			•••••	
FROM	TO	m wellLITHOLO		FROM	TO TO		OG (cont.) or PLU			
0	35	Silt/clay	010 100	110111		DITIO, D				
35	39.5	Weathered shale (bas	sed on CPT							
		electronic readings)	4							
 									·	
	<u> </u>				· · · · · · · · · · · · · · · · · · ·					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged										
under my jurisdiction and was completed on (mo/day/year) .11/9/2010 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 680. This Water Well Record was completed on (po/day/year) 10/08/2012 under the business name of Delta Environmental by (signature) 1										
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check, the expect answers. Send three copies										
(white, bl	ue, pink) t	o Kansas Depar tment of Heal	th and E nvironment, Bureau	of Water, Geol	ogy Section	on, 1000 SW Ja	ckson St., Suite 420,	Topeka, Ka	nsas 666 12-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy										