WATER V	WELL RECORD	Form W	WC-5	Division of W	ater Resources App. N	0.	
	TION OF WATER WEI			Section Number	Township No.	Range Number	
	McPherson	1/4 SE 1/4 SE		<del></del>	T 21 S	R 4 DE VW	
		cation; if unknown, distance a	Global Positioning System (GPS) information: Latitude: .38.22520084 (in decimal degrees)				
from nearest town or intersection: If at owner's address, check here  NW from intersection of South Main Street and Farmington Road.  MW11.				Longitude: 97.77595598 (in decimal degrees) Elevation: 1525.716			
2 WATER WELL OWNER: USDA - S. Gilmore - 0513, 4714-S				Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 1400 Independence Ave. SW				GPS unit (Make/Model:)			
City, State, ZIP Code : Washington, DC 20250-0513				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 41 ft.							
ı	SECTION BOX: Depth(s) Groundwater Encountered (1)						
SECTION BOX:  Depth(s) Groundwater Encountered (1)							
Pump test data: Well water was ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm							
W -NW - NE - Bore Hole Diameter 3.25 in. to .41 ft., and in. to							
SW -SE							
Was a chemical/bacteriological sample submitted to Department?  Yes  No							
S If yes, mo/day/yr sample was submitted							
water went districted: [1] Tes [2] No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .1							
Casing height above land surface -0.5 in., Weight 0.33 lbs./ft., Wall thickness or gauge No. Sch. 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot       ☑ Mill slot       ☐ Gauze wrapped       ☐ Torch cut       ☐ Drilled holes       ☐ None (open hole)         ☐ Louvered shutter       ☐ Key punched       ☐ Wire wrapped       ☐ Saw cut       ☐ Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From							
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other Flush mount Grout Intervals: From 3.0 ft. to .27 ft., From .27 ft. to .29 ft., From .3 ft. to .0.5 in. ft.							
What is the nearest source of possible contamination:  ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Scepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well  Direction from well							
		OLOGIC LOG	FROM			JGGING INTERVALS	
0 34							
34 41							
ļ	electronic readin	gs)					
						<u>*</u>	
				***************************************			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .11/10/2010 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No680 This Water Well Record was completed on (mo/day/year) .10/08/2012							
under the business name of Delta Environmental by (signature) h							
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at <a href="http://www.kdheks.gov/waterwell/index.html">http://www.kdheks.gov/waterwell/index.html</a> .							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							