WATER WEL	L RECORD	Form W	WC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL:		Fraction		Section Number Township No. Range Number	
County: McPherson		1/4 SE 1/4 SE			
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information: Latitude: .38,22547563	
from nearest town or intersection: If at owner's address, check here NW from intersection of South Main Street and Farmington Road.			Longitude: 97.77707714 (in decimal degrees)		
MW13.				Elevation: 1523.506 Datum: WGS 84, NAD 83, NAD 27	
2 WATER WELL OWNER: USDA - S. Gilmore - 0513, 4714-S RR#, Street Address, Box #: 1400 Independence Ave, SW			Collection Method: GPS unit (Make/Model:)		
City, State, ZIP Code : Washington, DC 20250-0513			☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey		
Washington, DC 20230-0313			Est. Accuracy:		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40.5 ft.					
1	SECTION BOX: Denth(s) Groundwater Encountered (1) ft (2) ft (3) ft				
N	N WELL'S STATIC WATER LEVEL. 22.84ft. below land surface measured on mo/day/yr. 2/16/2011				
Pump test data: Well water wasft. after					
V NW - - NE - EST. YIELD					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
swse Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well					
S If yes, mo/day/yr sample was submitted					
1 mile Water well disinfected? ☐ Yes ☑ No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter .1					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
Louvered shutter					
SCREEN-PERFORATED INTERVALS: From					
GRAVEL PACK INTERVALS: From 28.5 ft. to 40.5 ft., From ft. to ft.					
From					
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other Flush mount Grout Intervals: From 3.0 ft. to .26.5 ft., From .26.5 ft., From .3 ft. to .0.5 in. ft.					
What is the nearest source of possible contamination:					
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)					
Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Oil well/gas we					
	well			from well	
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
	Silt/clay	I ODT			
	Weathered shale (base electronic readings)	d on CP1			
	electronic readings)				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) .11/10/2010 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 680					
under the business name of Delta Environmental by (signature) by (signature)					
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the corplet answers. Send three copies					
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					