

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: McPherson		SW 1/4 NW 1/4 NW 1/4	15	T 21 S	R 5 EW
Distance and direction from nearest town or city street address of well if located within city? 5 mi. W 1/4 S of Inman					
2 WATER WELL OWNER:		LaMont Whitmore Rt 2 Inman, KS 67546			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 72 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 7-8-88 Pump test data: Well water was 50 ft. after 2 hours pumping 25 gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 74 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded			
Blank casing diameter 5 in. to 57 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 12 in. weight lbs./ft. Wall thickness or gauge No. 160					
TYPE OF SCREEN OR PERFORATION MATERIAL:		DPVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		B Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 6 Wire wrapped 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 57 ft. to 72 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 50 ft. to 74 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout B Bentonite 4 Other					
Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? 55			
Direction from well? NW					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	28	Br Clay			
28	56	Br & Gr Clay			
56	72	Sand & Rubble			
72	74	Br Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-8-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 6-4-89 under the business name of Miller Drilling by (signature) Egan Miller					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					