

1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number	
County: McPherson		NW 1/4 NW 1/4 NE 1/4	34	T 21 S	R 5 E	
Distance and direction from nearest town or city? 3 mi N, 1/2 W of Medora			Street address of well if located within city?			
2 WATER WELL OWNER: Wayne Neufeld						
RR#, St. Address, Box #: Rt 1			Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: Taman, KS 67546			Application Number:			
3 DEPTH OF COMPLETED WELL: 87 ft. Bore Hole Diameter: 10 in. to 90 ft. and in. to ft.						
Well Water to be used as:						
1 Domestic		3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well	
2 Irrigation		4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)	
			7 Lawn and garden only	10 Observation well		
Well's static water level: 28 ft. below land surface measured on 11 month 17 day 80 year						
Pump Test Data: Well water was 34 ft. after 12 hours pumping 20 gpm						
Est. Yield 40 gpm: Well water was ft. after hours pumping gpm						
4 TYPE OF BLANK CASING USED:						
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	Casing Joints: Glued <input checked="" type="checkbox"/> Clamped	
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	
			7 Fiberglass		Threaded	
Blank casing dia 6 in. to 72 ft. Dia in. to ft. Dia in. to ft.						
Casing height above land surface 16 in. weight 3.35 lbs./ft. Wall thickness or gauge No 160						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)	
					12 None used (open hole)	
Screen or Perforation Openings Are:						
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes		
			7 Torch cut	10 Other (specify)		
Screen-Perforation Dia 6 in. to 87 ft. Dia in. to ft. Dia in. to ft.						
Screen-Perforated Intervals: From 72 ft. to 87 ft. From ft. to ft. From ft. to ft.						
Gravel Pack Intervals: From 60 ft. to 89 ft. From ft. to ft. From ft. to ft.						
5 GROUT MATERIAL:						
1 Neat cement		2 Cement grout	3 Bentonite	4 Other		
Grouted Intervals: From 3 ft. to 13 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank		4 Cess pool	7 Sewage lagoon	10 Fuel storage	14 Abandoned water well	
2 Sewer lines		5 Seepage pit	8 Feed yard	11 Fertilizer storage	15 Oil well/Gas well	
3 Lateral lines		6 Pit privy	9 Livestock pens	12 Insecticide storage	16 Other (specify below)	
Direction from well NE How many feet 60 ? Water Well Disinfected? Yes <input checked="" type="checkbox"/> No						
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, date sample was submitted month day year Pump Installed? Yes <input checked="" type="checkbox"/> No						
If Yes: Pump Manufacturer's name 51208 Valley Model No. 50208 HP 1/2 Volts 230						
Depth of Pump Intake 50 ft. Pumps Capacity rated at 12 gal./min.						
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other						
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 11 month 24 day 80 year						
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 382						
This Water Well Record was completed on 3 month 8 day 81 year under the business name of Miller Water Well Service by (signature) Egna Miller						
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		LITHOLOGIC LOG		LITHOLOGIC LOG		
		FROM	TO	FROM	TO	
		0	34	Br Clay		
		34	40	F Sand		
		40	56	Br Clay		
		56	62	Silty Br Clay		
		62	72	Br & Gr Clay		
	72	Sand & Rubble				
	87	Red Shale				
ELEVATION:						
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)						

OFFICE USE ONLY

T

R

E

SEC.

34

NW 1/4

NE 1/4

SE 1/4