


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County McPherson	Fraction NW 1/4 NE 1/4 NW 1/4	Section number 35	Township number T 21 S R 5 E	Range number 5
2. Distance and direction from nearest town or city: 3 mi N, 1/4 E		3. Owner of well: Sam Lewis		R.R. or street: RA 5		
Street address of well location if in city: Medora, KS		City, state, zip code: Hutchinson, KS 67501				
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 10 in. Completion date 8-9-77 Well depth 78 ft.		
		Howe sewer 170' X		7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input checked="" type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Black Top Soil		0	4	<input checked="" type="checkbox"/> Casing: Material PVC Height: above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight sch 40 lbs./ft. Dia. 6 in. to 78 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. <input type="checkbox"/>		
Brown clay		4	24	10. Screen: Manufacturer's name J+L Type PVC Dia. 6 Slot gauge 030 Length 30' Set between 48 ft. and 78 ft. ft. and <input type="checkbox"/> ft.		
Sand + silt		24	35	Gravel pack? Yes Size range of material F-1/2		
rocky Rubble		35	38	11. Static water level: <input type="checkbox"/> mo./day/yr. 14 ft. below land surface Date 8-9-77		
dark gray clay		38	50	12. Pumping level below land surfaces: 23 ft. after 2 hrs. pumping 25 g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 35 g.p.m.		
Fine sand + silt		50	77	13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date 8-11-77		
red shale		77	80	14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade		
				15. Well grouted? Yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 3 ft. to 13 ft.		
				16. Nearest source of possible contamination: ft. 70 Direction N Type sewer Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Valley Steel Model number 51206 HP 1/3 Volts 270 Length of drop pipe 35 ft. capacity 12 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:		20. Water well contractor's certification:		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		High Nitrates - 143 ppm		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Miller Water Well 137 Business name License No. Address Hutchinson, KS Signed Joe Miller 6-15-78 Authorized representative Date		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5