


1 LOCATION OF WATER WELL: County: <u>McPherson</u>		Fraction <u>SE 1/4 NE 1/4 NE 1/4</u>	Section Number <u>2</u>	Township Number <u>T 21 S</u>	Range Number <u>R 5 EW</u>
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: <u>Martin Doakson</u> RR#, St. Address, Box # : <u>585 FIFTH AVE</u> City, State, ZIP Code : <u>ANDAMAN, KS 67440</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <u>90</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>70</u> ft. 2. ft. 3. <u>7-21-98</u> ft. WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>70</u> ft. after <u>1</u> hours pumping <u>30</u> gpm Est. Yield <u>204</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>12</u> in. to <u>40</u> ft. and <u>5</u> in. to <u>90</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? <u>Yes</u> No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>40</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>14</u> in. weight <u>50R 26</u> lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>35</u> ft. to <u>40</u> ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>E</u> How many feet? <u>100</u>					
FROM TO		LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
<u>0 4</u>		<u>Top Soil</u>			
<u>4 40</u>		<u>Clay</u>			
<u>40 90</u>		<u>Shale</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-21-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>980</u> This Water Well Record was completed on (mo/day/yr) <u>7-25-98</u> under the business name of <u>Carl Ornel</u> by (signature) <u>[Signature]</u>					